

**CHAPTER 15
TWO-LANE HIGHWAYS**

CONTENTS

1. INTRODUCTION..... 15-1

 Overview..... 15-1

 Chapter Organization..... 15-1

 Related HCM Content..... 15-2

2. CONCEPTS 15-3

 Characteristics of Two-Lane Highways..... 15-3

 Capacity and LOS 15-6

3. CORE MOTORIZED VEHICLE METHODOLOGY 15-10

 Scope of the Methodology 15-10

 Required Data and Sources 15-11

 Overview of the Methodology 15-12

 Computational Steps 15-14

 Facility Analysis..... 15-28

 Other Performance Measures..... 15-29

4. EXTENSIONS TO THE MOTORIZED VEHICLE METHODOLOGY 15-31

 Passing Lanes 15-31

 Climbing Lanes 15-36

 Design and Operational Treatments 15-37

5. BICYCLE METHODOLOGY 15-42

 Scope of the Methodology 15-42

 Required Data and Sources 15-43

 Overview of the Methodology 15-44

 Computational Steps 15-45

6. APPLICATIONS..... 15-48

 Example Problems 15-48

 Related Content in the HCMAG..... 15-48

 Example Results 15-49

 Generalized Daily Service Volumes..... 15-53

 Design Analysis..... 15-54

 Planning and Preliminary Engineering Analysis 15-55

 Use of Alternative Tools..... 15-55

7. REFERENCES..... 15-56

LIST OF EXHIBITS

Exhibit 15-1 Two-Lane Highway Classifications Illustrated	15-5
Exhibit 15-2 Speed–Flow and PTSF Relationships for Directional Segments with Base Conditions	15-7
Exhibit 15-3 Motorized Vehicle LOS for Two-Lane Highways.....	15-8
Exhibit 15-4 Bicycle LOS for Two-Lane and Multilane Highways.....	15-9
Exhibit 15-5 Required Input Data, Potential Data Sources, and Default Values for Two-Lane Highway Motorized Vehicle Analysis	15-12
Exhibit 15-6 Flowchart of the Core Two-Lane Highway Methodology	15-13
Exhibit 15-7 Adjustment Factor for Lane and Shoulder Width (f_{LS}).....	15-16
Exhibit 15-8 Adjustment Factor for Access Point Density (f_A).....	15-16
Exhibit 15-9 ATS Grade Adjustment Factor ($f_{g,ATS}$) for Level Terrain, Rolling Terrain, and Specific Downgrades	15-17
Exhibit 15-10 ATS Grade Adjustment Factor ($f_{g,ATS}$) for Specific Upgrades.....	15-18
Exhibit 15-11 ATS Passenger Car Equivalents for Trucks (E_T) and RVs (E_R) for Level Terrain, Rolling Terrain, and Specific Downgrades.....	15-19
Exhibit 15-12 ATS Passenger Car Equivalents for Trucks (E_T) on Specific Upgrades	15-20
Exhibit 15-13 ATS Passenger Car Equivalents for RVs (E_R) on Specific Upgrades	15-20
Exhibit 15-14 ATS Passenger Car Equivalents (E_{TC}) for Trucks on Downgrades Traveling at Crawl Speed	15-21
Exhibit 15-15 ATS Adjustment Factor for No-Passing Zones ($f_{np,ATS}$)	15-22
Exhibit 15-16 PTSF Grade Adjustment Factor ($f_{g,PTSF}$) for Level Terrain, Rolling Terrain, and Specific Downgrades.....	15-24
Exhibit 15-17 PTSF Grade Adjustment Factor ($f_{g,PTSF}$) for Specific Upgrades	15-24
Exhibit 15-18 PTSF Passenger Car Equivalents for Trucks (E_T) and RVs (E_R) for Level Terrain, Rolling Terrain, and Specific Downgrades.....	15-24
Exhibit 15-19 PTSF Passenger Car Equivalents for Trucks (E_T) and RVs (E_R) on Specific Upgrades	15-25
Exhibit 15-20 PTSF Coefficients for Use in Equation 15-10 for Estimating BPTSF.....	15-26
Exhibit 15-21 No-Passing-Zone Adjustment Factor ($f_{np,PTSF}$) for Determination of PTSF	15-26
Exhibit 15-22 Operational Effect of a Passing Lane on PTSF.....	15-31
Exhibit 15-23 Downstream Length of Roadway Affected by Passing Lanes on Directional Segments in Level and Rolling Terrain.....	15-32

Exhibit 15-24 Optimal Lengths of Passing Lanes on Two-Lane Highways	15-33
Exhibit 15-25 Effect of a Passing Lane on PTSF	15-33
Exhibit 15-26 Adjustment Factor for the Impact of a Passing Lane on PTSF ($f_{pl,PTSF}$)	15-34
Exhibit 15-27 Impact of a Passing Lane on ATS.....	15-35
Exhibit 15-28 Adjustment Factor for Estimating the Impact of a Passing Lane on ATS ($f_{pl,ATS}$).....	15-35
Exhibit 15-29 Adjustment Factors (f_{pl}) for Estimating ATS and PTSF Within a Climbing Lane	15-37
Exhibit 15-30 Typical Turnout Illustrated.....	15-38
Exhibit 15-31 Typical Two-Lane Highway Intersection with Left-Turn Lane.....	15-39
Exhibit 15-32 Illustrative Effect of Turning Delays at Intersections on PTSF	15-40
Exhibit 15-33 Typical Shoulder Bypass Lane at a Three-Leg Intersection on a Two-Lane Highway	15-40
Exhibit 15-34 Typical TWLTL on a Two-Lane Highway	15-41
Exhibit 15-35 Estimated Delay Reduction with a TWLTL on a Two-Lane Highway Without Paved Shoulders.....	15-41
Exhibit 15-36 Required Input Data, Potential Data Sources, and Default Values for Two-Lane and Multilane Highway Bicycle Analysis	15-44
Exhibit 15-37 Flowchart of the Bicycle Methodology for Two-Lane and Multilane Highways.....	15-44
Exhibit 15-38 Illustrative Effect of Volume and Shoulder Width on ATS and PTSF	15-49
Exhibit 15-39 Illustrative Effect of Volume and Percent No-Passing Zones on ATS and PTSF	15-50
Exhibit 15-40 Illustrative Effect of Volume and General Terrain Type on ATS and PTSF.....	15-50
Exhibit 15-41 Illustrative Effect of Volume and Passing Lane Location on ATS and PTSF.....	15-51
Exhibit 15-42 Illustrative Effect of Volume and Passing Lane Length on ATS and PTSF.....	15-51
Exhibit 15-43 Illustrative Effect of Volume, Lane Width, and Shoulder Width on BLOS Score	15-52
Exhibit 15-44 Illustrative Effect of Volume, Speed Limit, and Heavy Vehicles on BLOS Score	15-53
Exhibit 15-45 Illustrative Effect of Volume, Pavement Condition, and On- Highway Parking on BLOS Score.....	15-53
Exhibit 15-46 Generalized Daily Service Volumes for Two-Lane Highways	15-54