

VOLUME 2 INDEX

The index to Volume 2 lists the text citations of the terms defined in the Glossary (Volume 1, Chapter 9). Volumes 1, 2, and 3 are separately indexed. In the index listings, the first number in each hyphenated pair of numbers indicates the chapter, and the number after the hyphen indicates the page within the chapter.

A

Acceleration lane, 14-4, 14-10, 14-15, 14-25, 14-27, 14-30 to 14-32, 14-34, 14-38 to 14-41
 Access point, 10-7 to 10-9, 10-31, 10-47, 10-50, 12-9, 12-18, 12-21, 12-22, 12-25, 12-27, 12-28, 12-31, 12-47, 12-48, 13-12, 15-11, 15-12, 15-15, 15-16, 15-49, 15-50, 15-51, 15-54
 Accuracy, 10-19, 10-48, 11-42
 Active bottleneck, 10-13, 10-29, 10-43, 14-6
 Active traffic and demand management (ATDM), 10-1 to 10-3, 10-21, 10-39, 10-51, 10-52, 11-1 to 11-4, 11-13, 11-14, 11-19, 11-23, 11-26, 11-30 to 11-38, 11-41, 12-8, 12-22, 12-23, 12-57
 Adjacent friction effect, 10-51, 13-32, 13-33, 14-36
 Adjustment factor, 10-28, 10-30, 10-31, 10-44, 10-46, 11-12, 11-27 to 11-29, 11-32, 11-34, 11-37, 11-43, 11-47, 12-8, 12-23, 12-25, 12-31, 12-33, 12-34, 12-41, 13-13, 13-19, 13-23, 13-24, 13-28, 13-31, 14-10, 14-15, 14-24, 14-33, 15-15 to 15-18, 15-21 to 15-24, 15-26 to 15-28, 15-34 to 15-36
 Algorithm, 10-1, 10-20, 10-35, 10-46, 10-57, 10-61, 11-1, 11-36, 12-24, 12-28, 12-61, 13-14, 13-18, 13-22, 13-25, 13-26, 13-28, 14-16 to 14-18, 14-20, 14-43
 All-way STOP-controlled (AWSC), 10-19
 Alternative tool, 10-32, 10-47, 10-57, 10-58, 10-60 to 10-62, 11-1, 11-46, 11-47, 12-23, 12-24, 12-57, 12-59, 13-11, 13-38 to 13-40, 14-43 to 14-46
 Analysis hour, 11-11, 12-52, 13-11, 13-37, 14-41, 14-42, 15-17
 Analysis period, 10-6, 10-15, 10-17, 10-19, 10-21, 10-23, 10-26, 10-29, 10-39, 10-40, 10-47, 10-48, 10-57, 10-59, 11-6, 11-10 to 11-13, 11-15 to 11-17, 11-19, 11-28, 11-29, 11-32 to 11-34, 11-45 to 11-47, 12-22, 12-51, 13-13, 13-22, 13-24, 14-10, 14-12, 15-2, 15-7, 15-10, 15-12, 15-28, 15-29, 15-42, 15-44
 Analytical model, 10-21, 11-25
 Annual average daily traffic (AADT), 11-16, 11-20, 11-21, 11-25, 12-44, 12-50, 12-52, 14-42, 15-43, 15-55
 Area type, 10-15, 10-20, 10-40, 10-41, 11-21

Automobile, 10-2, 12-1, 12-2, 12-15, 12-16, 12-25, 12-35, 12-38, 12-45, 12-58, 13-1, 14-1
 Auxiliary lane, 10-3, 10-7, 10-24, 10-30, 10-52, 12-58, 13-4, 13-6, 13-8, 13-32
 Average grade, 15-21
 Average travel speed, 15-1, 15-22, 15-29, 15-35

B

Barrier, 10-38, 10-40, 10-41, 10-43 to 10-45, 10-47, 10-49, 11-12, 12-12 to 12-14, 12-23, 12-29, 12-30, 12-43, 12-57, 13-4, 13-18, 15-6, 15-56
 Base capacity, 10-31, 11-43, 12-8, 12-32, 12-33, 12-39, 14-5, 14-22, 15-28
 Base conditions, 10-10, 11-20, 11-21, 11-23, 11-45, 12-1, 12-7 to 12-10, 12-34, 12-39, 12-51, 14-1, 14-5, 14-12, 15-5, 15-6, 15-14, 15-16 to 15-18, 15-25 to 15-27, 15-30
 Base dataset, 11-15, 11-16, 11-18, 11-21, 11-45
 Base free-flow speed, 10-20, 11-17, 11-43, 12-22, 12-25, 12-27, 12-28, 12-46 to 12-48, 15-12, 15-15, 15-49, 15-50, 15-51
 Base length, 10-4, 10-26, 13-4, 13-11
 Base scenario, 11-6, 11-9, 11-11, 11-16, 11-18, 11-20, 11-21, 11-23, 11-25 to 11-29, 11-33
 Basic freeway segment, 10-2 to 10-5, 10-7, 10-10, 10-14 to 10-16, 10-24, 10-26, 10-27, 10-30, 10-41, 10-44, 10-45, 10-47, 10-53, 10-56, 10-60, 11-2, Chapter 12, 13-3, 13-10, 13-13, 13-20 to 13-22, 13-24, 14-5, 14-8, 14-11, 14-23, 14-28, 14-30, 14-34, 14-45 to 14-47
 Bicycle, 12-1, 12-2, 12-21, 12-43 to 12-45, 12-62, 15-1 to 15-3, 15-7, 15-9, 15-42 to 15-48, 15-52, 15-57
 Bicycle facility, 12-44, 15-7, 15-42
 Bicycle lane, 15-2, 15-42
 Bicycle level of service, 15-9, 15-47, 15-52, 15-53
 Bottleneck, 10-3, 10-13, 10-14, 10-17 to 10-19, 10-30, 10-32, 10-33, 10-35 to 10-37, 10-43, 10-47, 10-58, 10-59, 11-13, 11-19, 11-21, 11-26, 12-1, 12-5, 12-6, 12-18, 12-21, 12-61, 14-6, 14-22, 14-24, 15-6, 15-14
 Breakdown, 10-2, 10-4, 10-11, 10-12, 10-14, 10-16, 10-17, 10-29, 10-43, 11-31, 12-4, 12-6, 12-7, 12-18, 12-39, 13-21, 13-22, 14-4, 14-6, 14-14, 14-22, 14-26, 14-36, 14-48

Buffer 1 managed lane segment, 12-40
 Bus stop, 12-23, 12-57
 Bypass lane, 15-40

C

Calibration, 10-6, 10-29 to 10-31, 10-39, 10-48, 10-52, 10-58, 10-60, 11-26, 11-30, 11-36, 11-38, 11-43, 12-8 to 12-10, 12-16, 12-31 to 12-33, 12-41, 12-42, 12-60, 12-61, 13-12, 13-20, 13-23, 13-39, 13-40, 14-6, 14-20, 14-23, 14-24, 14-34, 14-44, 14-46, 15-4
 Capacity, 10-1 to 10-3, 10-7, 10-8, 10-10 to 10-14, 10-18 to 10-21, 10-23, 10-29 to 10-33, 10-35 to 10-38, 10-40 to 10-57, 10-59, 10-60, 10-63, 11-2 to 11-4, 11-6, 11-7, 11-9, 11-11 to 11-13, 11-17 to 11-20, 11-31 to 11-34, 11-39, 11-41, 11-43, 11-44, 11-46 to 11-48, 12-1, 12-2, 12-5 to 12-10, 12-12, 12-14, 12-16, 12-18, 12-19, 12-21 to 12-25, 12-27, 12-32 to 12-35, 12-38 to 12-43, 12-45, 12-47, 12-48, 12-57 to 12-59, 12-61, 12-62, 13-1, 13-2, 13-4, 13-8, 13-10, 13-11, 13-13 to 13-15, 13-20 to 13-24, 13-31 to 13-41, 14-2, 14-5 to 14-7, 14-9 to 14-13, 14-22 to 14-26, 14-31 to 14-37, 14-39 to 14-48, 15-1, 15-2, 15-6 to 15-11, 15-27, 15-28, 15-30 to 15-32, 15-37, 15-48, 15-50, 15-54, 15-56
 Capacity adjustment factor (CAF), 10-20, 10-30, 10-31, 10-44, 10-56, 10-57, 10-60, 11-12, 11-13, 11-27 to 11-29, 11-34, 11-37, 11-43, 11-47, 12-2, 12-9, 12-10, 12-16, 12-27, 12-33, 12-41, 12-47, 12-49, 13-2, 13-13, 13-23, 13-31, 14-2, 14-6, 14-10 to 14-12, 14-22, 14-24
 Centerline, 12-4, 15-6
 Class I two-lane highway, 15-4, 15-8, 15-48
 Class II two-lane highway, 15-4, 15-23, 15-25
 Class III two-lane highway, 15-4, 15-16, 15-21, 15-27, 15-29, 15-41, 15-44
 Climbing lane, 12-57, 15-10, 15-11, 15-31, 15-36, 15-37, 15-54
 Cloverleaf interchange, 12-47, 13-26
 Composite grade, 12-2, 12-16, 12-21, 12-35, 12-38
 Computational engine, 10-1, 10-2, 10-19, 10-29, 10-51, 10-53, 11-1, 11-6, 11-10, 11-12, 11-18, 11-24, 11-28, 11-29, 11-35, 11-37, 11-45
 Congestion, 10-3, 10-13, 10-17, 10-18, 10-23, 10-28, 10-30, 10-32, 10-39, 10-40, 10-49, 10-58, 11-4, 11-8, 11-18, 11-27, 11-32, 11-34, 11-39, 11-40, 11-46, 12-7 to 12-9, 12-22, 13-12, 14-5, 14-6, 14-8, 15-9, 15-14, 15-37
 Congestion pricing, 11-46, 12-22
 Continuous access managed lane segment, 12-49
 Control condition, 10-11, 10-13
 Corridor, 10-62, 11-4, 12-4
 Crawl speed, 10-40, 10-46, 12-35, 15-19, 15-21, 15-24

Critical density, 10-49
 Critical segment, 10-11, 10-13, 10-14, 10-54
 Cross weave, 10-8
 Crossover, 10-42, 10-45

D

Daily service volume, 10-10, 12-51, 12-52, 12-54, 15-53, 15-55
 Deceleration lane, 10-20, 10-27, 13-4, 14-3 to 14-6, 14-8, 14-10 to 14-12, 14-15, 14-16, 14-18, 14-19, 14-22, 14-26 to 14-28, 14-30 to 14-32, 14-35, 14-39 to 14-41, 14-43, 14-45
 Default value, 10-20, 10-29 to 10-31, 11-10, 11-16, 11-18, 11-21, 11-26, 11-27, 11-37, 11-42, 11-44, 11-45, 12-7, 12-24, 12-25, 12-27, 12-41, 12-48 to 12-50, 13-4, 13-13, 13-14, 13-37, 14-9, 14-10, 14-23, 14-42, 14-46, 15-11, 15-12, 15-14, 15-43 to 15-45, 15-55
 Delay, 10-18, 10-19, 10-38, 10-47, 10-56, 11-13, 11-45, 12-24, 13-39, 14-44, 15-1, 15-3, 15-8, 15-39 to 15-41
 Demand adjustment factor (DAF), 10-30, 10-31, 10-52, 11-17, 11-21, 11-26 to 11-29, 11-34, 11-37, 13-36
 Demand flow rate, 10-11 to 10-13, 10-27, 10-32, 10-34, 11-4, 12-4, 12-9, 12-19, 12-22, 12-34, 12-39, 12-40, 12-50, 13-1, 13-10, 13-11, 13-16 to 13-19, 13-21, 13-24, 13-25, 13-29, 13-31, 13-38, 14-4, 14-7, 14-11 to 14-13, 14-15, 14-25 to 14-28, 14-35, 14-36, 14-40, 14-43, 15-6, 15-10, 15-14 to 15-17, 15-20 to 15-28, 15-30, 15-31, 15-33 to 15-35, 15-42, 15-45, 15-47, 15-54
 Demand multiplier, 11-11, 11-16, 11-21, 11-25, 11-26, 11-28, 11-29, 11-45
 Demand starvation, 10-33, 13-12
 Demand volume, 10-7, 10-20, 10-31, 10-48, 12-21, 12-22, 12-25 to 12-27, 12-33, 12-34, 12-39, 12-50, 12-51, 13-12, 13-13, 13-18, 13-38, 13-40, 14-10, 14-12, 14-15, 14-41 to 14-43, 15-12, 15-14, 15-16, 15-23, 15-29
 Demand-to-capacity ratio, 10-12, 10-13, 10-16, 10-19, 10-31 to 10-33, 10-48, 10-54 to 10-58, 11-39, 12-1, 12-18, 13-36
 Density, 10-8, 10-10, 10-14 to 10-16, 10-18, 10-29, 10-30, 10-34 to 10-36, 10-38, 10-39, 10-41, 10-44, 10-49, 10-51, 10-56 to 10-60, 11-6, 11-7, 12-2, 12-6, 12-8 to 12-10, 12-14, 12-16 to 12-19, 12-21 to 12-25, 12-27, 12-28, 12-30, 12-31, 12-35, 12-38 to 12-43, 12-46 to 12-49, 12-58, 12-59, 13-1, 13-2, 13-4, 13-5, 13-9 to 13-11, 13-16, 13-21, 13-22, 13-24, 13-26, 13-28 to 13-30, 13-37, 13-39, 13-40, 14-1, 14-2, 14-7 to 14-9, 14-12 to 14-14, 14-16, 14-25, 14-26, 14-28 to 14-30, 14-33, 14-35, 14-36, 14-38 to 14-41, 14-43 to 14-47, 15-3, 15-4, 15-12, 15-15, 15-16, 15-41

Design analysis, 12-45, 12-50, 13-37, 14-40 to 14-42, 15-54, 15-55
 Design speed, 12-25, 12-28, 13-13, 14-10, 15-12, 15-15, 15-16
 Detector, 10-6, 12-58, 12-59, 13-13, 14-46, 14-47
 Deterministic model, 12-24
 D-factor, 12-50, 12-52, 12-54, 14-42, 15-55
 Diamond interchange, 10-3, 12-47, 13-26
 Directional design hour volume, 13-37
 Directional distribution, 12-50, 15-27, 15-28
 Directional flow rate, 15-36
 Directional split, 15-26, 15-49 to 15-51
 Diverge, 10-1 to 10-5, 10-7, 10-9 to 10-11, 10-14, 10-15, 10-17, 10-20, 10-23 to 10-27, 10-30, 10-37, 10-45, 10-47, 10-49, 10-56, 10-59, 10-60, 11-1, 11-2, 11-5, 12-1 to 12-4, 12-9, 12-14, 13-1 to 13-4, 13-6, 13-8, 13-12, 13-21, 13-24, 13-30, Chapter 14, 15-1
 Diverge segment, 10-2 to 10-4, 10-7, 10-10, 10-11, 10-14, 10-15, 10-20, 10-23, 10-24, 10-26, 10-30, 10-45, 10-47, 10-49, 10-56, 10-59, 10-60, 11-2, 13-2, 13-6, 13-8, 13-21, Chapter 14
 Driver population, 10-2, 10-20, 10-30, 10-31, 10-60, 11-25, 12-2, 12-7, 12-25, 12-27, 12-31 to 12-33, 13-13, 13-23, 14-10 to 14-12, 14-23, 14-24, 14-27, 15-16

E

Environmental conditions, 10-31
 Expected demand, 10-35
 Extent of congestion, 10-57, 12-24, 13-12, 14-9, 14-44
 External section, 10-4

F

Facility, Chapter 10, Chapter 11, 12-1, 12-2, 12-7 to 12-9, 12-19, 12-23 to 12-25, 12-27, 12-31, 12-36, 12-41, 12-44, 12-52, 12-56, 12-60, 13-1, 13-2, 13-9, 13-12, 13-14, 13-28, 13-32, 13-33, 13-37, 13-39, 14-1, 14-3, 14-5, 14-6, 14-8 to 14-11, 14-15, 14-22, 14-26, 14-28, 14-35, 14-36, 14-44, 15-1, 15-3, 15-4, 15-6, 15-9, 15-10, 15-14 to 15-16, 15-27 to 15-29, 15-42, 15-43, 15-48, 15-54
 Flow rate, 10-10 to 10-12, 10-14, 10-27, 10-29, 10-33, 10-35, 10-43, 10-44, 10-59 to 10-61, 11-16, 11-47, 12-6 to 12-9, 12-12, 12-14, 12-16 to 12-19, 12-22, 12-27, 12-33, 12-34, 12-41 to 12-43, 12-48, 12-51, 12-58, 13-11 to 13-13, 13-18, 13-19, 13-22, 13-37, 13-38, 14-7, 14-14 to 14-18, 14-20 to 14-22, 14-25, 14-28, 14-29, 14-33, 14-42, 14-43, 15-6, 15-8, 15-14, 15-16, 15-17, 15-21, 15-23, 15-27, 15-28, 15-32
 Follower density, 15-11

Free-flow speed (FFS), 10-1, 10-5, 10-6, 10-10, 10-14, 10-18, 10-20, 10-27, 10-30, 10-31, 10-40, 10-41, 10-44 to 10-49, 10-54, 10-56, 10-60, 10-61, 11-4 to 11-6, 11-9, 11-13, 11-16, 11-17, 11-20, 11-34, 11-39, 11-43 to 11-45, 11-47, 12-6 to 12-10, 12-12, 12-14, 12-15, 12-17, 12-18, 12-22 to 12-25, 12-27 to 12-32, 12-39 to 12-42, 12-46 to 12-59, 12-61, 13-1, 13-13, 13-14, 13-16, 13-22, 13-26, 13-28 to 13-30, 13-35, 13-36, 14-3, 14-6, 14-10, 14-11, 14-15, 14-16, 14-23, 14-27, 14-28, 14-38 to 14-41, 14-43, 14-45 to 14-47, 15-1, 15-8 to 15-10, 15-12, 15-14 to 15-16, 15-21, 15-22, 15-27, 15-36, 15-51, 15-54
 Free-flow travel time, 10-58, 11-5, 11-7, 11-8
 Freeway, Chapters 10-14, 15-2, 15-31, 15-48
 Freeway auxiliary lane, 13-5 to 13-8
 Freeway facility, Chapter 10, Chapter 11, 12-2, 12-8, 12-16, 12-18, 12-19, 12-23, 12-45, 13-2, 13-24, 13-32 to 13-34, 13-37, 13-39, 14-2, 14-6, 14-8, 14-22, 14-26, 14-28, 14-36, 14-37
 Freeway facility capacity, 10-11, 10-13
 Freeway junction, 12-21, 14-3, 14-4, 14-8, 14-31, 14-32, 14-40, 14-42
 Freeway section, 10-3, 10-4, 10-6, 10-21, 10-23, 10-26, 11-46, 14-8
 Freeway segment capacity, 10-14, 12-6, 13-23, 14-24
 Freeway weaving segment, 10-2, 10-3, 11-2, Chapter 13

G

Gap, 10-60, 10-61, 12-18, 14-31, 15-1, 15-6, 15-8, 15-39
 Gap acceptance, 10-60, 10-61
 General purpose lane, 10-1, 10-8, 10-24, 10-31, 10-38, 10-46, 10-47 to 10-51, 11-20, 12-1, 12-12, 12-14, 12-40 to 12-43, 12-49, 13-12, 13-31 to 13-33, 14-35, 14-36
 General terrain, 12-21, 12-34, 12-35, 15-10, 15-19, 15-23, 15-24, 15-50
 Gore area, 10-7, 10-38, 13-4, 13-8, 13-18, 13-31, 14-31
 Growth factor, 10-52

H

Headway, 10-60, 11-47, 12-24, 12-33, 12-58, 12-59, 14-9, 14-39, 14-40, 14-47, 15-8
 Heavy vehicle, 10-20, 10-40, 10-45, 10-46, 10-48, 10-61, 12-1, 12-2, 12-7, 12-8, 12-15, 12-16, 12-25, 12-27, 12-32, 12-34, 12-35, 12-43, 12-44, 12-47, 12-49, 12-52, 12-54, 12-58, 12-59, 13-13, 13-19, 13-24, 13-37, 13-38, 14-5, 14-6, 14-10 to 14-12, 14-15, 14-41, 14-43, 14-45, 14-46, 15-9, 15-12, 15-15, 15-16, 15-18, 15-21, 15-23, 15-24, 15-28, 15-36, 15-38, 15-42 to 15-44, 15-47, 15-52, 15-53

Hidden bottleneck, 10-13
 High-occupancy vehicle (HOV), 10-1, 10-46,
 11-33, 12-1, 12-12, 12-60, 14-9, 14-44, 14-47

I

Incident, 10-3, 10-18, 10-28, 10-30, 10-31,
 10-36, 10-49, 10-57, 10-60, 11-1, 11-3, 11-4,
 11-6, 11-8 to 11-13, 11-16, 11-17, 11-19 to
 11-22, 11-25 to 11-29, 11-31, 11-32, 11-36,
 11-37, 11-39, 11-40, 11-41, 11-44 to 11-48,
 12-5, 12-7, 12-8, 12-17, 12-18, 12-22, 12-23,
 12-32, 12-33, 12-41, 12-48, 12-57, 12-60, 13-1,
 13-13, 13-14, 13-23, 13-28, 14-6, 14-10, 14-23,
 14-24, 15-6
 Incident clearance time, 11-4, 11-32
 Incident delay, 11-45
 Influence area, 10-3 to 10-5, 10-7, 10-9, 10-23
 to 10-26, 12-3, 12-4, 13-11, 13-21, 14-1, 14-4,
 14-5, 14-7, 14-8, 14-12 to 14-19, 14-21, 14-22,
 14-24 to 14-32, 14-35, 14-41 to 14-43, 14-45,
 14-46
 Inputs, 10-2, 10-20, 10-28, 10-29, 10-32, 10-44,
 10-48, 10-54, 11-6, 11-9, 11-10, 11-12, 11-16,
 11-20, 11-21, 11-26, 11-28, 11-32, 11-37 to
 11-39, 11-45, 12-2, 12-24, 12-46, 12-59, 13-2,
 13-14, 13-19, 13-35, 13-37, 13-40, 14-2, 14-10,
 14-15, 14-36, 14-38, 14-46, 15-2, 15-12, 15-49,
 15-55
 Intelligent transportation system (ITS), 12-22,
 12-57, 13-12, 14-9, 14-44
 Interchange, 10-4, 10-6, 10-10, 10-19, 10-62,
 12-46, 12-47, 13-6, 13-13, 13-17, 13-18, 13-25
 to 13-27, 13-30, 13-34 to 13-36, 14-5, 14-8,
 14-15, 14-23, 14-25, 14-37
 Interchange density, 13-13, 13-17, 13-25 to
 13-27, 13-35, 13-36
 Interchange ramp terminal, 14-25
 Internal section, 10-3
 Intersection delay, 15-39
 Interval, 10-21, 10-23, 10-28, 10-32 to 10-39,
 10-43, 10-59, 12-7, 12-35, 13-11, 15-37, 15-39
 Isolated intersection, 15-11

J

Jam density, 10-20, 10-29, 11-26

K

K-factor, 12-50, 14-42

L

Lane 1, 14-5, 14-31
 Lane addition, 10-18, 12-23, 14-16, 14-24,
 14-30, 15-33
 Lane balance, 13-8, 13-9

Lane distribution, 10-61, 12-57, 14-15, 14-16,
 14-18, 14-32
 Lane group, 10-8, 10-24, 10-38, 10-39, 10-47 to
 10-49, 13-32
 Lane utilization, 14-44
 Lane width, 10-7, 10-10, 10-20, 10-27, 10-41,
 10-48, 10-49, 10-60, 12-1, 12-7, 12-9, 12-21,
 12-24, 12-25, 12-27, 12-28, 12-32, 13-11,
 13-18, 14-11, 15-5, 15-10, 15-12, 15-42, 15-44,
 15-46, 15-49 to 15-53
 Lateral clearance, 10-7, 10-10, 10-20, 10-27,
 10-43, 10-45, 10-46, 10-48, 12-1, 12-7, 12-9,
 12-21, 12-25, 12-27 to 12-30, 12-32, 12-46 to
 12-48, 14-5, 14-11
 Level of service (LOS), 10-1, 10-3, 10-13 to
 10-18, 10-25, 10-34, 10-39, 10-51, 10-53,
 10-56 to 10-59, 11-30, 12-1, 12-2, 12-14,
 12-16 to 12-22, 12-26, 12-35, 12-39, 12-43 to
 12-45, 12-50 to 12-58, 12-61, 13-1, 13-9 to
 13-11, 13-14, 13-15, 13-18, 13-24, 13-28 to
 13-30, 13-34, 13-37, 13-38, 14-1, 14-4, 14-5,
 14-7, 14-8, 14-12 to 14-14, 14-23 to 14-26,
 14-28, 14-31, 14-34 to 14-37, 14-41 to 14-43,
 15-1 to 15-3, 15-6 to 15-10, 15-12, 15-16,
 15-21, 15-23, 15-25, 15-27, 15-29 to 15-32,
 15-36 to 15-38, 15-42 to 15-44, 15-46 to
 15-48, 15-51 to 15-55
 Level-of-service score (LOS score), 12-43,
 12-44, 15-2, 15-42, 15-46, 15-47
 Level terrain, 10-26, 12-35, 15-6, 15-17, 15-19,
 15-21, 15-23, 15-24, 15-38, 15-49 to 15-51,
 15-53, 15-54
 Link, 10-57, 12-58, 13-40, 14-45 to 14-47, 15-3,
 15-4

M

Macroscopic model, 13-40
 Mainline, 10-18, 10-20, 10-27, 10-28, 10-30,
 10-34 to 10-37, 11-4, 11-5, 12-25, 13-3, 13-6,
 14-1, 14-3, 14-4, 14-6, 14-7, 14-10, 14-11,
 14-22, 14-35, 14-36, 14-38 to 14-40, 14-47
 Mainline output, 10-36
 Major diverge area, 14-34, 14-35
 Major merge area, 14-34
 Major weaving segment, 13-6, 13-8, 13-9,
 13-34
 Managed lane, 10-1, 10-3, 10-7 to 10-10, 10-20
 to 10-22, 10-24, 10-31, 10-38, 10-46 to 10-51,
 10-53, 10-58, 11-3, 11-16, 11-19, 11-20, 11-28,
 11-31, 11-33, 12-1, 12-2, 12-12, 12-14, 12-21,
 12-40 to 12-43, 12-45, 12-52, 13-1, 13-12,
 13-30 to 13-33, 14-35, 14-36, 14-44
 Maximum weaving length, 13-2, 13-39
 Median, 11-5, 11-7, 11-18, 12-4, 12-9, 12-23,
 12-25, 12-28 to 12-31, 12-35, 12-47, 12-48,
 12-57, 15-40
 Meeting, 10-63, 11-7, 11-48

Merge, 10-2 to 10-5, 10-7, 10-8 to 10-11, 10-14, 10-15, 10-17, 10-20, 10-23 to 10-27, 10-30, 10-45, 10-47, 10-49, 10-50, 10-56, 10-59, 10-60, 11-2, 11-5, 11-32, 12-2 to 12-4, 12-9, 12-18, 13-2 to 13-4, 13-6, 13-9, 13-12, 13-21, 13-24, 13-30, Chapter 14

Merge segment, 10-3, 10-4, 10-7, 10-24, 10-45, 13-1, Chapter 14

Microscopic model, 12-58, 13-39, 14-45

Mobility, 15-3, 15-7

Mode, 10-2, 11-3, 13-34, 13-37, 14-37, 14-41, 15-2, 15-7, 15-9, 15-49, 15-52, 15-54

Model, 10-16, 10-17, 10-19, 10-26, 10-28, 10-39, 10-40, 10-43 to 10-46, 10-48, 10-51, 10-59, 10-60, 11-30, 11-38, 11-39, 11-47, 12-9, 12-16, 12-24, 12-35, 12-38, 12-40, 12-44, 12-58, 12-59, 13-14, 13-22, 13-25 to 13-28, 13-39, 13-40, 14-4, 14-6, 14-16, 14-17, 14-19, 14-20, 14-22, 14-34, 14-35, 14-45, 14-48, 15-11, 15-33, 15-42 to 15-44, 15-57

Motorized vehicle mode, 13-2, 14-2

Mountainous terrain, 12-35, 15-10

Multilane highway, 10-2, 11-2, Chapter 12, 13-1, 13-9, 13-10, 13-29, 13-30, 14-1, 14-3, 14-7, 14-8, 14-11, 14-15, 14-23, 15-2, 15-6, 15-9, 15-42, 15-44, 15-45

Multiple weaving segment, 13-1, 13-12, 13-30, 13-39

N

Node, 10-34 to 10-37

Nonrecurrent congestion, 10-49, 11-1, 11-3, 11-19, 11-26, 12-5

Non-severe weather, 11-11, 11-43

Nonweaving flow, 10-60, 13-12, 13-23, 13-26, 13-27

Nonweaving movement, 13-3, 13-39, 13-40

No-passing zone, 15-5, 15-6, 15-11, 15-12, 15-21 to 15-23, 15-25 to 15-27, 15-41, 15-49 to 15-51, 15-54

O

Off-ramp, 10-3, 10-4, 10-7 to 10-10, 10-19, 10-20, 10-23 to 10-25, 10-27, 10-30, 10-32, 10-34, 10-36, 10-37, 10-48, 10-50, 12-4, 12-23, 12-46, 13-5 to 13-8, 13-13, 13-16, 13-31, 13-32, 13-34, 13-39, 13-40, Chapter 14

Off-street, 15-42

One-sided weaving segment, 13-5, 13-7, 13-9, 13-14, 13-19, 13-20

On-ramp, 10-3, 10-4, 10-7 to 10-10, 10-20, 10-23 to 10-25, 10-27, 10-30 to 10-32, 10-34, 10-36 to 10-38, 10-50, 10-52, 11-4, 11-13, 12-4, 12-23, 13-5, 13-6, 13-8, 13-9, 13-12, 13-13, 13-16, 13-24, 13-31, 13-32, 13-38, Chapter 14

On-time arrival, 11-7

Operational analysis, 10-20, 10-48, 10-53, 10-56, 11-39, 12-24, 12-26, 12-27, 12-45, 12-50, 13-18, 13-34, 13-37, 14-37, 14-40, 14-41, 14-44, 15-28, 15-32, 15-36, 15-37, 15-54, 15-55

Opposing flow rate, 15-8, 15-21, 15-23

Outputs, 10-36, 10-58, 11-14, 11-20, 11-36, 12-57, 12-58, 13-14, 13-37, 13-39, 13-40, 14-12, 14-41, 14-42, 14-44, 14-45, 15-11

Oversaturated flow, 10-30, 10-56, 10-58, 12-5, 14-8

P

Passenger car, 10-10, 10-40, 10-46, 10-61, 12-7, 12-9, 12-16, 12-19, 12-27, 12-32 to 12-35, 12-39, 12-50, 12-51, 12-58, 13-16, 13-18, 13-23, 13-24, 13-29, 13-38 to 13-40, 14-6, 14-12, 14-15, 14-43, 14-45, 14-46, 15-5, 15-14, 15-18, 15-19, 15-21, 15-23, 15-24, 15-26

Passenger-car equivalent (PCE), 12-16, 12-34 to 12-38, 12-58, 12-62, 14-45, 14-46

Passing lane, 12-23, 15-1, 15-2, 15-11, 15-12, 15-31 to 15-39, 15-45, 15-48 to 15-51, 15-54

Passing sight distance, 15-6

Pavement condition rating, 15-53

Peak hour, 10-1, 10-48, 11-46, 11-47, 12-22, 12-25, 12-34, 12-50, 13-11 to 13-13, 13-19, 13-37, 13-38, 14-10, 14-12, 14-15, 14-42, 15-12, 15-17, 15-29, 15-44, 15-45

Peak hour factor (PHF), 10-48, 11-47, 12-22, 12-25, 12-27, 12-34, 12-52 to 12-56, 13-12 to 13-14, 13-19, 13-35 to 13-38, 14-10 to 14-12, 14-15, 14-41 to 14-43, 15-12, 15-14, 15-17, 15-23, 15-27, 15-29, 15-44, 15-45, 15-49 to 15-54

Pedestrian, 12-23, 12-57, 15-2, 15-42

Percent of free-flow speed, 15-8

Percent time-spent-following, 15-1, 15-25, 15-29, 15-34

Percentile travel time index, 11-5, 11-46

Performance measure, 10-2, 10-18, 10-33, 10-35, 10-38, 10-39, 10-54, 10-57 to 10-59, 11-1, 11-2, 11-4, 11-7, 11-8, 11-14, 11-15, 11-17 to 11-19, 11-29 to 11-31, 11-38, 11-39, 11-44, 12-2, 12-19, 12-22, 12-24, 12-46, 12-59, 13-1, 13-2, 13-12, 13-32, 13-35, 13-39, 13-40, 14-1, 14-2, 14-26, 14-36, 14-38, 14-44, 14-45, 15-1, 15-2, 15-10, 15-11, 15-13, 15-16, 15-23, 15-27, 15-29, 15-30, 15-42, 15-49, 15-55

Phase, 13-37

Planning and preliminary engineering analysis, 10-53, 11-39, 12-45, 12-50, 14-42, 15-54, 15-55

Planning time index, 11-7

Platoon, 12-1, 13-30, 14-3, 14-36, 15-1, 15-3, 15-6, 15-8, 15-9, 15-38

Point, 10-3 to 10-9, 10-12, 10-13, 10-21, 10-24 to 10-27, 10-35, 10-37, 10-50, 10-56, 10-58, 10-60, 11-4 to 11-6, 11-8, 11-20, 11-21, 12-4, 12-17, 12-18, 12-21, 12-23, 12-25, 12-31, 12-39, 12-44, 12-47, 12-48, 12-57, 12-58, 13-3, 13-4, 13-20, 13-31, 13-39, 13-40, 14-1, 14-4, 14-8, 14-11, 14-15, 14-16, 14-19, 14-22, 14-24, 14-43, 14-44, 14-46, 15-10 to 15-12, 15-15, 15-16, 15-27, 15-34, 15-42 to 15-45, 15-47, 15-48, 15-51, 15-55

Postbreakdown flow rate, 10-14, 10-29, 12-7

Prevailing condition, 10-31, 10-43, 10-44, 12-5, 12-7, 12-33, 12-34, 12-51, 12-52, 13-14, 13-18, 13-22 to 13-24, 15-14, 15-18, 15-27, 15-28

Progression, 15-11

Q

Quality of service, 11-3, 15-43, 15-46, 15-54

Queue, 10-5, 10-6, 10-12 to 10-15, 10-17 to 10-20, 10-22, 10-23, 10-28 to 10-30, 10-35 to 10-39, 10-43, 10-45 to 10-48, 10-54, 10-55, 10-58, 10-59, 10-63, 11-18, 11-26, 11-39, 12-5 to 12-7, 12-18, 12-24, 13-24, 13-39, 13-40, 14-3, 14-6 to 14-8, 14-14, 14-24, 14-25, 14-44

Queue discharge capacity drop, 10-20, 10-29, 11-26

Queue discharge flow, 10-14, 10-43, 10-46, 11-39, 12-5, 12-7, 14-6

Queue length, 10-38, 10-58, 12-24, 14-44

Queue spillback, 10-39, 12-18

Queue storage ratio, 14-3, 14-24

R

Ramp, 10-3, 10-5, 10-7 to 10-10, 10-18 to 10-20, 10-24, 10-25, 10-27, 10-30, 10-32, 10-36 to 10-38, 10-40, 10-41, 10-44, 10-48, 10-50 to 10-52, 10-56, 10-60 to 10-62, 11-3, 11-13, 11-31, 11-32, 11-33, 11-46, 12-1, 12-18, 12-21 to 12-23, 12-25, 12-27, 12-28, 12-30, 12-46, 12-47, 12-57, 12-62, Chapter 13, Chapter 14

Ramp meter, 10-18, 10-51, 11-3, 11-32, 11-33, 11-46, 12-22, 12-57, 13-12, 13-38, 14-9, 14-36, 14-44, 14-47

Ramp roadway, 10-30, 10-37, 10-38, 10-52, 14-3, 14-4, 14-7, 14-11, 14-22, 14-23, 14-25, 14-36

Ramp weave, 13-6, 13-35, 13-36

Ramp-freeway junction, 10-27, 14-1, 14-3 to 14-5, 14-7 to 14-9, 14-11, 14-12, 14-14, 14-15, 14-22 to 14-25, 14-30 to 14-32, 14-37, 14-40 to 14-43

Ramp-street junction, 10-32, 14-3, 14-7, 14-25

Recovery, 10-14, 10-29, 10-37, 12-6, 12-7, 15-38

Recreational vehicle (RV), 10-61, 12-15, 12-34, 15-18 to 15-20, 15-24, 15-25

Recurring congestion, 11-32, 11-39, 12-18

Regression model, 12-44, 13-14

Reliability rating, 11-7, 11-19, 11-29

Reliability reporting period, 11-1, 11-6, 11-18, 11-45

Right-of-way, 12-4

Roadside obstruction, 12-29

Roadway characteristic, 12-44, 15-42

Rolling terrain, 12-35, 12-52, 12-54, 15-17, 15-19, 15-28, 15-31, 15-50, 15-53

Roundabout, 10-19, 12-21, 12-57

Rubbernecking, 12-5

Rural, 10-15, 10-16, 10-20, 10-41, 10-43, 10-63, 11-21, 11-27, 11-42, 12-3, 12-4, 12-19, 12-24, 12-25, 12-36, 12-44, 12-50, 12-52, 12-54, 12-56, 12-61, 13-13, 13-14, 14-10, 15-3, 15-4, 15-34, 15-37, 15-41, 15-43

S

Saturation headway, 11-47

Scenario, 10-11, 10-12, 10-24, 10-40, 10-42, 10-52, 10-56, 11-1, 11-2, 11-6, 11-8 to 11-18, 11-20, 11-25 to 11-29, 11-32 to 11-39, 11-41, 11-46, 11-47, 13-34, 14-40 to 14-42

Scenario generation, 11-1, 11-2, 11-8 to 11-11, 11-13, 11-16 to 11-18, 11-20, 11-25 to 11-28, 11-33, 11-37

Section, 10-3 to 10-7, 10-10 to 10-12, 10-20, 10-21, 10-23 to 10-25, 10-29, 10-39, 10-56, 10-57, 11-46, 12-41, 12-42, 14-7, 14-8, 14-43, 15-3, 15-19, 15-28, 15-37, 15-48

Seed file, 11-6, 11-9

Segment, 10-1 to 10-8, 10-10 to 10-21, 10-23 to 10-39, 10-41, 10-44 to 10-51, 10-54 to 10-62, 11-1, 11-2, 11-4 to 11-6, 11-9, 11-10, 11-12, 11-13, 11-16, 11-19 to 11-22, 11-27 to 11-29, 11-32, 11-39, 11-43, Chapters 12-15

Segment initialization, 10-35

Sensitivity analysis, 10-52

Service flow rate, 10-10, 12-50 to 12-52, 13-38, 14-37, 14-42, 14-43, 15-10, 15-32

Service measure, 10-20, 10-25, 10-38, 12-19, 12-25, 12-43, 13-11, 13-13, 13-14, 14-10, 14-45, 15-7, 15-10, 15-12, 15-27, 15-36, 15-51

Service volume, 10-2, 10-10, 10-56, 12-2, 12-47, 12-51, 12-52, 12-56, 13-2, 13-34, 13-37, 13-38, 14-2, 14-37, 14-42, 14-43, 15-2, 15-32, 15-48, 15-53

Severe weather, 11-3, 11-11, 11-32, 11-43, 12-8, 12-45, 14-6

Shared lane, 15-2, 15-42

Shared-use path, 15-2

Shock wave, 10-33, 10-36 to 10-38

Short length, 10-26, 13-4, 13-13, 13-16, 13-20, 13-25, 13-35, 13-36, 15-8

Shoulder, 10-18, 10-41, 10-42, 10-49, 10-51, 10-57, 10-60, 11-3, 11-10, 11-12, 11-13, 11-21, 11-22, 11-28, 11-29, 11-32, 11-41, 11-44, 12-22, 12-41, 12-44, 12-46, 12-48, 13-18, 15-2, 15-5, 15-6, 15-10, 15-12, 15-15, 15-16, 15-34, 15-37 to 15-46, 15-49 to 15-54, 15-57

Shoulder bypass lane, 15-40
 Shy distance, 15-45
 Simple weaving segment, 13-12, 13-30
 Simulation, 10-17, 10-19, 10-57 to 10-62, 11-19, 11-47 to 11-49, 12-24, 12-38, 12-57 to 12-60, 12-62, 13-11, 13-12, 13-38 to 13-40, 14-8, 14-9, 14-44 to 14-47, 15-11
 Single-unit truck, 10-27, 10-61, 12-15, 12-16, 12-34, 12-36 to 12-38
 Space, 10-1, 10-12, 10-13, 10-16 to 10-19, 10-21, 10-23, 10-28, 10-31 to 10-34, 10-39, 10-57, 10-59, 11-5, 11-7, 11-17, 11-20, 12-9, 12-18, 12-19, 12-22, 12-38, 12-40, 12-41, 12-58, 13-4, 13-5, 13-28, 13-29, 14-25, 14-26, 14-38, 14-45, 15-45
 Space mean speed, 10-18, 10-34, 10-57, 11-7, 12-9, 12-19, 12-22, 12-38, 12-40, 12-41, 12-58, 13-28, 13-29, 14-45
 Spacing, 10-5, 10-7, 12-4, 12-8, 15-48
 Special event, 11-1, 11-3, 11-17, 11-19, 11-21, 11-22, 11-26, 11-27, 11-39, 11-45, 15-6
 Specific grade, 10-20, 10-27, 13-13, 14-10, 14-11, 14-41, 15-10, 15-12, 15-17, 15-31, 15-36
 Speed, 10-10, 10-14, 10-18, 10-20, 10-21, 10-29, 10-30, 10-31, 10-34, 10-37, 10-38, 10-40 to 10-42, 10-44, 10-46, 10-48 to 10-52, 10-54, 10-56 to 10-59, 10-61, 10-63, 11-3, 11-4, 11-7, 11-11, 11-12, 11-18, 11-19, 11-22, 11-31 to 11-34, 11-43, 11-45 to 11-48, 12-1, 12-2, 12-4 to 12-7, 12-9 to 12-12, 12-14 to 12-22, 12-24, 12-25, 12-27, 12-28, 12-31, 12-33, 12-35, 12-38 to 12-44, 12-47 to 12-50, 12- to 12-62, 13-1, 13-2, 13-4, 13-11 to 13-14, 13-16, 13-20, 13-24, 13-26, 13-28 to 13-30, 13-35 to 13-37, 13-39, 13-40, 14-1 to 14-3, 14-7 to 14-14, 14-16, 14-23, 14-25 to 14-29, 14-33, 14-34, 14-36, 14-38 to 14-41, 14-44 to 14-47, 15-1, 15-3, 15-4, 15-6 to 15-9, 15-12, 15-14, 15-15, 15-17, 15-19, 15-21, 15-22, 15-35, 15-36, 15-38, 15-39, 15-42 to 15-44, 15-46, 15-47, 15-52 to 15-54
 Speed adjustment factor (SAF), 10-30, 10-31, 10-44, 10-45, 10-50, 10-52, 11-11 to 11-13, 11-17, 11-26 to 11-29, 11-34, 11-37, 11-43, 12-9, 12-10, 12-16, 12-22, 12-31, 12-41, 12-47 to 12-49, 13-13, 13-28, 14-10, 14-27
 Speed harmonization, 11-3, 11-31, 12-22
 Split, 10-26, 10-27, 10-49, 12-16, 13-8, 14-31, 14-34, 14-43, 15-12, 15-26, 15-27, 15-44
 Start-up lost time, 11-47
 Stochastic model, 12-24
 Study period, 10-3, 10-21, 10-39, 10-52, 11-5, 11-6, 11-8, 11-11 to 11-13, 11-17, 11-18, 11-21, 11-22, 11-45
 Suburban street, 12-44, 15-41, 15-43
 System, 10-1, 10-6, 10-60, 10-61, 11-4, 11-31 to 11-33, 11-36, 11-46, 12-23, 12-25, 12-62, 13-6, 13-37, 13-39, 15-1, 15-3, 15-21, 15-57

T

Target speed, 11-29
 Terrain, 10-7, 10-20, 10-26, 10-27, 10-46, 10-48, 10-61, 12-21, 12-25, 12-27, 12-34, 12-35, 12-52 to 12-56, 13-13, 14-10, 14-11, 14-41, 15-4, 15-10, 15-12, 15-17, 15-19, 15-23, 15-24, 15-32, 15-34, 15-42, 15-50, 15-53, 15-54
 Through vehicles, 14-5, 14-18, 15-39, 15-41
 Throughput, 10-30, 10-37, 10-60, 11-4, 12-6 to 12-8, 12-58, 12-59, 14-46, 14-47
 Time interval, 10-13, 10-14, 10-18 to 10-21, 10-28 to 10-30, 10-32 to 10-39, 10-52, 10-58, 10-59, 11-6, 12-7, 12-57, 14-44
 Time interval scale factor, 10-28, 10-29
 Time mean speed, 10-57
 Time-space, 10-18, 10-19, 10-21, 10-23, 10-28, 10-29, 10-31 to 10-33, 10-39, 10-52, 11-12
 Tool, 10-17, 10-19, 10-29, 10-31, 10-32, 10-43, 10-53, 10-57 to 10-62, 11-26, 11-28, 11-31, 11-33, 11-46, 11-47, 12-45, 12-57, 12-59, 12-60, 13-11, 13-12, 13-34, 13-38 to 13-40, 14-9, 14-37, 14-44, 14-45, 14-47, 15-11, 15-48, 15-55
 Total lateral clearance, 12-28 to 12-30
 Total ramp density, 10-10, 10-20, 10-41, 10-48, 12-21, 12-25, 12-28, 12-30, 12-46, 12-47, 13-26, 14-11
 Tractor trailer, 12-15, 12-16, 12-34, 12-36 to 12-38
 Traffic analysis tool, 10-57, 11-46, 12-57, 13-28, 14-43
 Traffic composition, 12-34
 Traffic condition, 10-30, 11-5, 12-4, 12-21
 Traffic control device, 10-3, 12-1, 13-1, 15-1, 15-11
 Traffic delay, 10-58
 Transition, 10-7, 10-35, 12-6, 12-57
 Travel mode, 11-31
 Travel speed, 14-39, 14-40, 15-8, 15-46
 Travel time, 10-18, 10-23, 10-54 to 10-56, 10-58, 11-1, 11-3 to 11-9, 11-15, 11-17 to 11-21, 11-29, 11-30, 11-36, 11-38, 11-39, 11-41, 11-44 to 11-46, 12-12, 14-44, 15-1, 15-7, 15-10, 15-16, 15-21, 15-28, 15-29
 Travel time distribution, 11-1, 11-3, 11-5 to 11-8, 11-15, 11-17, 11-19, 11-29, 11-30, 11-38, 11-41
 Travel time index, 11-5, 11-6, 11-45, 11-46
 Travel time reliability, Chapter 11
 Traveler information systems, 12-22
 Traveler perception model, 12-43, 15-9, 15-42
 Truck, 10-10, 10-27, 10-61, 11-33, 12-1, 12-2, 12-7, 12-15, 12-16, 12-21, 12-27, 12-34 to 12-36, 12-38, 12-43, 12-45, 12-53 to 12-57, 12-62, 13-40, 14-6, 14-11, 14-12, 15-5, 15-9, 15-10, 15-18, 15-19, 15-21, 15-24, 15-36, 15-49 to 15-51, 15-54
 Turn lane, 12-25, 15-37, 15-39, 14-40

Turnout, 15-37, 15-38
 Two-lane highway, 12-23, 12-43, 12-44, 12-57,
 14-8, Chapter 15
 Two-sided weaving segment, 13-5 to 13-7,
 13-9, 13-14, 13-17 to 13-20, 13-22, 13-34
 Two-way left-turn lane (TWLTL), 12-4, 12-23,
 12-25, 12-30, 12-45, 12-57, 15-37, 15-40,
 15-41
 Two-way STOP-controlled (TWSC), 10-19

U

Uncontrolled, 12-5, 14-3, 14-7, 14-8
 Undersaturated flow, 10-23, 10-32, 12-5, 15-1
 Undivided highway, 12-30
 Uninterrupted flow, 12-1, 12-4, 12-5, 12-9
 Unsignalized intersection, 12-31, 14-1, 14-25,
 15-16, 15-34, 15-39
 Urban, 10-5, 10-15, 10-16, 10-20, 10-41, 11-21,
 11-27, 11-42, 12-3, 12-19, 12-23 to 12-25,
 12-34, 12-36, 12-44, 12-46, 12-50, 12-52 to
 12-55, 12-60, 12-61, 13-12 to 13-14, 14-1,
 14-10, 15-1, 15-2, 15-11, 15-41 to 15-43,
 15-48
 Urban street, 13-12, 14-1, 15-1, 15-2, 15-11,
 15-42, 15-48

V

Validation, 10-6, 10-30, 10-39, 11-38
 Variability, 11-3, 11-7 to 11-11, 11-17, 11-19,
 11-25, 11-26, 11-33, 11-42, 12-24, 12-58,
 14-45
 Volume, 10-2, 10-10 to 10-12, 10-18, 10-20,
 10-31, 10-37, 10-56, 11-21, 11-46, 12-2, 12-4,
 12-9, 12-16, 12-18, 12-22, 12-25, 12-31, 12-33,
 12-34, 12-43, 12-44, 12-50, 12-52 to 12-54,
 12-56, 13-2, 13-11, 13-13, 13-16, 13-18, 13-21,
 13-23, 13-34, 13-35, 13-37, 13-38, 13-40, 14-2,
 14-10, 14-15, 14-16, 14-22, 14-30, 14-36 to
 14-38, 14-42, 14-43, 15-1, 15-2, 15-6, 15-7,
 15-9, 15-12, 15-14, 15-17, 15-32, 15-37, 15-39
 to 15-46, 15-48 to 15-53
 Volume-to-capacity ratio, 10-18, 11-46, 12-19,
 12-22, 12-47, 13-23, 13-34, 14-25, 14-34,
 14-37, 15-10, 15-11, 15-30, 15-54

W

Weaving, 10-3 to 10-5, 10-7 to 10-11, 10-14,
 10-15, 10-17, 10-19, 10-20, 10-23 to 10-27,
 10-30, 10-45, 10-47 to 10-51, 10-56, 10-59,
 10-60, 11-5, 11-20, 12-2 to 12-5, 12-9, 12-18,
 12-32, Chapter 13, 14-2, 14-5, 14-8, 14-16,
 14-18, 14-20, 14-24, 14-30, 14-34, 14-37,
 14-42
 Weaving configuration, 10-25, 10-26, 13-6,
 13-8, 13-11, 13-22, 13-25
 Weaving flow, 10-8, 10-9, 13-9, 13-18, 13-21,
 13-22
 Weaving length, 13-26, 13-27, 13-29
 Weaving movement, 10-8, 12-4, 13-3, 13-5 to
 13-9, 13-12, 13-14, 13-17, 13-19, 13-30, 13-31
 Weight-to-power ratio, 12-15
 Work zone, 10-1, 10-3, 10-18, 10-28, 10-30,
 10-40 to 10-46, 10-52, 10-53, 10-57, 10-60,
 11-1, 11-3, 11-6, 11-8 to 11-13, 11-16, 11-17,
 11-19 to 11-22, 11-26, 11-28, 11-31, 11-32,
 11-36, 11-37, 11-39, 11-44, 11-45, 12-7, 12-8,
 12-22, 12-23, 12-27, 12-29, 12-31, 12-33,
 12-41, 13-23, 13-28, 14-6, 14-24, 14-27, 15-2,
 15-31