

## VOLUME 3 INDEX

The index to Volume 3 lists the text citations of the terms defined in the Glossary (Volume 1, Chapter 9). Volumes 1, 2, and 3 are separately indexed. In the index listings, the first number in each hyphenated pair of numbers indicates the chapter, and the number after the hyphen indicates the page within the chapter.

### A

- Acceleration lane, 18-71
- Access point, 16-30, 18-6, 18-13, 18-15 to 18-19, 18-21, 18-22, 18-25 to 18-28, 18-30 to 18-33, 18-38, 18-59, 18-60, 18-64, 18-82, 19-33, 23-35
- Accessibility, 16-10, 18-10, 22-30, 24-28
- Accuracy, 16-4, 16-9, 18-4, 18-9, 18-14, 18-25, 18-43, 18-59, 18-67, 18-80, 19-14, 19-22, 19-73, 19-87, 19-94, 23-29, 23-72, 23-85
- Active access point, 18-16, 18-18, 18-19
- Active passings, 24-3, 24-17, 24-19 to 24-21, 24-25
- Active traffic and demand management (ATDM), 16-2, 17-2 to 17-6, 17-34, 17-36, 17-41, 17-42, 18-2
- Actuated control, 18-34, 19-4 to 19-6, 19-34, 19-38, 19-41, 19-50, 19-56, 19-76, 19-88, 23-29, 23-63
- Adjustment factor, 17-12, 17-13, 17-15, 17-18, 17-19, 18-2, 18-27 to 18-30, 18-32, 18-35, 18-52, 18-63, 19-2, 19-12, 19-23, 19-29 to 19-31, 19-45 to 19-49, 19-51, 19-84, 19-89, 19-90, 20-18, 20-19, 20-22, 20-24, 20-25, 20-27, 21-13, 21-16, 21-21, 22-13, 22-16, 22-21, 22-22, 23-27, 23-29, 23-31 to 23-33, 23-37, 23-38, 23-44, 23-78, 23-82, 23-85
- Algorithm, 17-35
- All-way STOP-controlled (AWSC), 16-17, 16-22, 16-29, 16-30, 18-23, 18-42, 18-43, 18-57, 18-58, Chapter 21, 22-9
- Alternative dataset, 17-9, 17-12, 17-15, 17-18, 17-22 to 17-25, 17-37
- Alternative intersection, 18-35, 23-1 to 23-6, 23-9, 23-17, 23-65, 23-70 to 23-73, 23-87
- Alternative tool, 16-32, 17-43, 17-44, 18-80 to 18-82, 19-94, 19-96, 20-1, 20-7 to 20-9, 20-37, 20-38, 21-1, 20-10, 22-3, 22-10 to 22-13, 22-24, 22-26, 23-2, 23-11, 23-12, 23-18, 23-19, 23-28, 23-50, 23-61, 23-63 to 23-65, 23-70, 23-79, 23-81, 23-82, 23-92
- Analysis hour, 24-12
- Analysis period, 16-1, 16-3, 16-5, 16-6, 16-10 to 16-13, 17-3, 17-7, 17-11, 17-12, 17-14, 17-17, 17-25 to 17-27, 17-29, 17-38, 17-39, 17-41, 17-43, 17-44, 18-1, 18-4, 18-5, 18-10 to 18-12, 18-14 to 18-17, 18-20, 18-21, 18-25, 18-27, 18-33, 18-44, 18-45, 18-59, 18-68, 18-69, 19-2, 19-4, 19-14, 19-18 to 19-20, 19-22 to 19-32, 19-34, 19-39, 19-49 to 19-53, 19-56, 19-65, 19-67 to 19-69, 19-73, 19-74, 19-87, 20-7, 20-10, 20-12, 20-20, 20-30, 20-32, 20-37, 21-10, 21-11, 21-18, 21-19, 22-3, 22-10, 22-14, 22-16, 22-23, 24-6, 24-14
- Analytical model, 20-30, 22-2, 22-3
- Annual average daily traffic (AADT), 16-6, 17-12, 17-15, 17-16, 23-93
- Approach delay, 19-24, 19-32
- Approach grade, 19-23, 19-34, 19-46, 20-10
- Area type, 17-23, 18-69, 19-24, 19-40, 19-45, 19-47, 23-29, 23-31
- Arrival rate, 16-11, 18-11, 19-13, 19-19, 19-62, 19-63, 19-64, 19-74, 21-5, 21-6
- Arrival type, 16-29, 19-28, 19-29, 23-29, 23-58, 23-76, 23-82
- Arrival-departure polygon, 18-37
- Automobile, 16-1, 16-9, 16-10, 16-16, 16-33, 18-1, 18-9, 18-10, 18-13, 18-39, 18-71, 18-83, 19-17, 19-18, 19-98, 20-4, 23-1, 24-28
- Average bicyclist, 24-19 to 24-22
- Average grade, 19-34
- Average running speed, 16-7, 17-9, 18-6, 18-27, 18-62
- Average travel speed, 23-13

**B**

Back of queue (BOQ), 19-20  
 Barrier, 18-46, 18-52, 18-53, 19-6, 19-7, 19-37, 19-38, 19-59, 19-60, 19-61, 24-1, 24-7  
 Barrier pair, 19-59 to 19-61  
 Base capacity, 17-9  
 Base conditions, 17-12, 17-24, 19-89  
 Base dataset, 17-7, 17-12, 17-23, 17-25, 17-26  
 Base free-flow speed, 16-7, 16-13 to 16-16, 17-9, 17-10, 17-27 to 17-30, 18-6, 18-7, 18-27 to 18-29, 18-38  
 Base saturation flow rate, 16-29, 16-30, 19-12, 19-23, 19-30, 19-44, 19-45, 19-89, 23-29, 23-31, 23-33  
 Baseline uniform delay, 19-68  
 Bicycle, 16-2, 16-4, 16-6, 16-8 to 16-10, 16-19, 16-22 to 16-25, 18-2, 18-4, 18-6 to 18-8, 18-10, 18-31, 18-44 to 18-46, 18-48, 18-50, 18-52, 18-53, 18-57 to 18-65, 18-83, 19-2, 19-14, 19-16, 19-18, 19-23, 19-31, 19-44, 19-45, 19-48, 19-76, 19-86 to 19-91, 19-98, 19-99, 20-3, 20-45, 20-50, 21-24, 22-8, 22-10, 22-11, 22-27, 23-1, 23-19, 23-29, 23-32, 23-50, 23-60, 23-65, 23-88, 23-89, Chapter 24  
 Bicycle facility, 16-24, 18-61, 24-1 to 24-3, 24-6, 24-7, 24-17, 24-25, 24-30, 24-33  
 Bicycle lane, 16-22, 16-23, 18-31, 18-44, 18-45, 18-52, 18-53, 18-57, 18-59, 18-60, 18-62, 18-64, 19-86 to 19-91, 21-24, 24-1  
 Bicycle level of service, 24-3, 24-5, 24-6, 24-8, 24-17, 24-18, 24-25, 24-30, 24-32, 24-33  
 Bicycle mode, 16-6, 18-6, 18-7, 19-14, 19-16, 19-88, 24-2, 24-9  
 Bicycle path, 24-1  
 Bicycle speed, 18-62, 24-9, 24-15, 24-16, 24-31, 24-32  
 Bottleneck, 17-23  
 Boundary intersection, 16-6 to 16-10, 16-13 to 16-20, 16-22 to 16-24, 16-27, 16-31, 18-3, 18-4, 18-6 to 18-8, 18-10, 18-12 to 18-15, 18-17 to 18-23, 18-25, 18-26, 18-29, 18-31 to 18-36, 18-38 to 18-45, 18-47, 18-51, 18-54, 18-57, 18-58, 18-61, 18-62, 18-67, 18-69 to 18-74, 18-79  
 Breakdown, 17-4, 17-20 to 17-22, 19-55, 21-26  
 Buffer width, 18-44, 18-46, 18-49, 18-52, 18-53  
 Bus shelter, 24-12  
 Bus stop, 18-38, 18-70, 19-23, 19-32, 19-47, 23-29  
 Bypass lane, 22-7, 22-8, 22-17 to 22-19, 22-22, 22-23, 22-28, 23-50

**C**

Calibration, 18-14, 18-28, 18-29, 18-43, 18-59, 18-67, 19-22, 19-73, 19-87, 19-98, 20-45, 22-1, 22-4, 22-5, 22-12, 22-13, 22-25, 22-27, 23-53  
 Call, 17-35, 17-36, 19-4, 19-37, 19-75  
 Capacity, 16-2, 16-7, 16-8, 16-11, 16-14, 16-16, 16-27, 16-33, 17-1, 17-3, 17-5 to 17-8, 17-10, 17-12, 17-30, 17-33, 17-34, 17-37, 17-40 to 17-42, 17-45, 18-2, 18-3, 18-6, 18-7, 18-10, 18-11, 18-15, 18-21 to 18-25, 18-27, 18-33, 18-37, 18-39, 18-66 to 18-68, 18-71, 18-80, 18-82, 18-83, 19-2, 19-3, 19-12, 19-15, 19-16, 19-18, 19-19, 19-22, 19-29 to 19-31, 19-38, 19-41, 19-44, 19-50 to 19-53, 19-55 to 19-59, 19-63, 19-65, 19-67 to 19-69, 19-83, 19-89, 19-92, 19-94, 19-96 to 19-99, 20-1 to 20-3, 20-6 to 20-9, 20-12, 20-14, 20-16, 20-19 to 20-38, 20-46, 20-49, 21-1, 21-3, 21-5 to 21-7, 21-9, 21-11, 21-17, 21-18, 21-20, 21-23, 21-25 to 21-27, 22-1 to 22-9, 22-11 to 22-15, 22-19 to 22-25, 22-28 to 22-31, 23-1, 23-2, 23-9, 23-10, 23-16, 23-19, 23-22, 23-26 to 23-28, 23-31, 23-50 to 23-56, 23-58, 23-60, 23-63, 23-65, 23-70, 23-77, 23-94 to 23-96, 24-1 to 24-4, 24-7, 24-11, 24-14 to 24-17, 24-25, 24-28, 24-35  
 Capacity adjustment factor (CAF), 20-22, 20-24, 20-25, 20-27, 20-34 to 20-36, 22-20, 22-21  
 Centerline, 16-13, 18-17, 18-19, 18-45, 18-47, 18-51, 18-61, 19-33, 23-26, 23-29, 23-46, 24-3, 24-9, 24-17, 24-25, 24-32  
 Central business district (CBD), 17-13, 18-44, 18-67, 18-69, 18-75, 18-76, 19-23, 19-24, 19-28, 19-40, 19-47, 23-29  
 Change interval, 19-36, 23-29, 23-39  
 Change period, 19-10 to 19-12, 19-36  
 Circulating flow, 22-2, 22-3, 22-17, 22-29  
 Circulation area, 16-18, 16-20, 19-1, 19-70, 19-71, 19-77, 19-80, 19-83, 24-27  
 Circulatory roadway, 22-5, 22-20, 22-21  
 Clearance interval, 19-36  
 Clearance lost time, 19-10 to 19-12, 19-14, 19-62  
 Clearance time, 17-20, 20-38, 20-39, 23-44, 23-82  
 Cloverleaf interchange, 23-27  
 Collector street, 16-6, 16-9, 16-12, 18-8, 18-16  
 Common green time, 23-39, 23-41, 23-42, 23-47, 23-48, 23-50  
 Compressed diamond interchange, 23-20  
 Computational engine, 17-8, 17-17, 17-25, 18-22, 19-41, 23-59, 23-60, 24-2, 24-34  
 Concurrency group, 19-7

- Conflict, 16-18, 18-43, 18-48, 18-64, 19-6, 19-26, 19-48, 19-71, 20-12 to 20-15, 20-31, 21-2 to 21-4, 21-6 to 21-8, 21-11, 21-15, 21-23, 22-2, 22-5, 22-16, 22-23, 23-1, 23-5, 23-6, 23-22, 23-44, 23-46, 23-59, 23-65, 23-68, 23-90, 24-4, 24-5, 24-27
- Conflicting approach, 21-2 to 21-9, 21-13, 21-15, 21-17
- Conflicting flow rate, 22-3, 22-4, 22-6, 23-51 to 23-54
- Conflicting movement, 19-6, 19-7, 19-11, 19-25, 19-67, 20-3, 20-13, 20-14, 20-16, 20-31, 20-36, 23-51, 23-58, 23-59
- Congestion, 16-7, 16-9, 16-12, 17-3, 17-6, 17-11, 17-28 to 17-32, 17-36, 17-40, 17-41, 17-43, 18-7, 18-9, 18-12, 18-13, 19-16, 19-19, 23-1
- Congestion pricing, 17-6, 17-36, 17-43
- Connected vehicle, 17-5, 17-34
- Control condition, 17-3, 17-22, 18-79, 19-93, 23-61
- Control delay, 16-7, 16-14, 16-19, 16-23, 16-27, 18-6, 18-15, 18-20, 18-23, 18-34, 18-35, 18-62, 18-70, 18-74, 19-1, 19-11, 19-15, 19-16, 19-20, 19-41, 19-49, 19-50, 19-53 to 19-55, 19-92, 19-95, 19-96, 20-2, 20-3, 20-6, 20-7, 20-9, 20-11, 20-28, 20-30 to 20-32, 20-46, 20-47, 21-9, 21-18, 21-19, 21-25, 22-9, 22-10, 22-22 to 22-24, 22-28, 22-29, 23-2, 23-3, 23-6, 23-12, 23-13, 23-16 to 23-18, 23-26, 23-28, 23-55, 23-56, 23-60, 23-70, 23-71, 23-77 to 23-80, 23-82 to 23-84, 23-86, 23-87, 23-91, 23-92, 23-94
- Controller, 17-4, 17-5, 17-11, 17-34, 19-4 to 19-7, 19-20, 19-34, 19-36 to 19-40, 19-51, 19-56, 19-99, 23-63
- Conventional diamond interchange, 23-20, 23-37
- Coordination, 17-5, 17-11, 18-80, 19-28, 19-36, 19-56, 19-76, 23-5, 23-58, 23-71
- Corridor, 17-3, 17-40, 19-3, 20-2, 22-8, 23-42
- Crawl speed, 18-36
- Critical headway, 18-70, 20-4 to 20-7, 20-10, 20-18 to 20-21, 20-39 to 20-42, 20-45, 20-47, 22-25, 23-3, 23-9 to 23-11, 23-51 to 23-53, 23-70, 23-77
- Critical phase, 19-11, 19-56, 19-58 to 19-62
- Critical platoon flow rate, 23-51
- Critical volume-to-capacity ratio, 16-8, 16-12
- Cross flow, 16-8, 18-8, 20-37, 20-38, 24-4, 24-6, 24-14
- Crossing time, 17-11, 19-36, 21-23
- Crossover, 23-5, 23-6, 23-8, 23-9, 23-22, 23-32, 23-36, 23-37, 23-44 to 23-47, 23-51 to 23-54, 23-57 to 23-59, 23-65 to 23-71, 23-73 to 23-80, 23-82, 23-83, 23-87, 23-89, 23-91, 23-93 to 23-97
- Crosswalk, 16-20, 18-21, 18-31, 18-38, 18-43, 18-44, 18-46, 18-47, 18-54, 18-55, 19-16, 19-31, 19-70, 19-71, 19-73, 19-75 to 19-77, 19-79 to 19-85, 19-99, 20-38 to 20-41, 21-23, 22-10, 22-11, 22-26, 24-1, 24-3
- Crosswalk occupancy time, 19-82, 19-83
- Cycle, 16-5, 16-12, 16-29, 16-30, 17-11, 17-35, 18-12, 18-27, 18-33, 18-34, 18-36, 18-37, 18-67, 18-70, 18-73, 19-4 to 19-6, 19-9, 19-11 to 19-13, 19-15, 19-20, 19-23 to 19-25, 19-27, 19-29, 19-37 to 19-39, 19-49, 19-51 to 19-56, 19-58 to 19-60, 19-62, 19-63, 19-65, 19-73, 19-76 to 19-78, 19-80, 19-82, 19-83, 19-87 to 19-89, 19-92, 19-95, 19-97, 20-8, 21-22, 21-23, 22-29, 23-9, 23-29, 23-32, 23-33, 23-41 to 23-44, 23-47 to 23-49, 23-52 to 23-55, 23-57, 23-59, 23-82, 23-83, 23-85, 23-90, 23-92
- Cycle failure, 18-37, 19-15, 19-29, 19-52
- Cycle length, 18-27, 18-34, 18-67, 18-70, 18-73, 19-4, 19-5, 19-9, 19-11, 19-12, 19-15, 19-23, 19-24, 19-27, 19-38, 19-49, 19-51, 19-56, 19-58, 19-73, 19-76 to 19-78, 19-87 to 19-89, 19-92, 19-95, 23-9, 23-29, 23-41, 23-42, 23-44, 23-48, 23-52 to 23-55, 23-57, 23-59, 23-82, 23-83, 23-85, 23-90, 23-92
- Cycle lost time, 19-11, 19-58 to 19-60, 19-62
- Cyclic spillback, 16-9, 16-12, 17-43, 18-9, 18-12, 18-26

## D

- Daily service volume, 16-29, 16-30, 18-79, 19-92
- De facto lane, 22-18
- Deceleration delay, 18-72, 18-73, 18-74
- Default value, 16-4, 16-31, 17-7, 17-12, 17-17, 17-19 to 17-21, 18-4, 18-14, 18-16, 18-19, 18-28, 18-43, 18-58, 18-59, 18-67, 18-79, 18-80, 19-14, 19-22, 19-24, 19-30, 19-32, 19-45, 19-72, 19-73, 19-76, 19-86 to 19-88, 19-93, 20-10, 20-11, 20-38, 21-10, 22-14, 23-29, 23-35, 23-53, 23-70, 23-72, 23-74, 23-76 to 23-78, 24-8, 24-9, 24-34
- Degree of saturation, 20-24, 20-30, 22-23
- Degree of utilization, 21-5 to 21-7, 21-9, 21-14, 21-17 to 21-20, 21-26
- Degree-of-conflict case, 21-7, 21-8, 21-16, 21-17, 21-21

- Delay, 16-2, 16-7, 16-11, 16-12, 16-16, 16-20, 16-24, 16-27, 17-2, 17-5, 17-9, 17-27 to 17-34, 18-2, 18-6, 18-7, 18-11 to 18-13, 18-15, 18-19 to 18-23, 18-27, 18-30 to 18-32, 18-34, 18-35, 18-38, 18-44, 18-47, 18-51, 18-54 to 18-56, 18-59, 18-61, 18-62, 18-70 to 18-75, 18-81, 19-1, 19-2, 19-7, 19-8, 19-11, 19-15, 19-16, 19-19, 19-20, 19-23, 19-25, 19-29, 19-30, 19-32, 19-41, 19-49 to 19-57, 19-62, 19-64 to 19-70, 19-79, 19-83 to 19-86, 19-89, 19-90, 19-94 to 19-99, 20-6, 20-7, 20-9, 20-21, 20-30 to 20-33, 20-37, 20-39 to 20-44, 20-47 to 20-49, 21-9, 21-18, 21-19, 21-22 to 21-24, 21-26, 21-27, 22-2, 22-9, 22-22, 22-23, 22-29, 23-1, 23-2, 23-6, 23-9, 23-12, 23-13, 23-16 to 23-18, 23-27, 23-28, 23-31, 23-45, 23-50, 23-55, 23-56, 23-60, 23-62, 23-65, 23-70, 23-71, 23-78, 23-79, 23-81, 23-83, 23-86, 23-88, 23-89, 23-92 to 23-94, 24-17
  - Delayed crossing, 20-41, 20-43
  - Delayed passing maneuver, 24-22
  - Demand adjustment factor (DAF), 17-15, 17-23, 17-26
  - Demand flow rate, 18-14, 18-15, 18-16, 18-17, 18-30, 18-32, 18-35, 18-52, 18-63, 18-64, 18-82, 19-22 to 19-24, 19-26, 19-30, 19-50, 19-52, 19-54, 19-59, 19-65, 19-67, 19-73, 19-74, 19-81, 19-84, 19-87, 19-91, 20-7, 20-10, 20-12, 21-10, 21-11, 22-14 to 22-16, 22-22, 23-32, 23-34, 23-55, 23-71, 23-73, 23-80
  - Demand multiplier, 23-91, 23-92
  - Demand starvation, 18-12, 19-20, 20-7, 21-10, 23-5, 23-10, 23-11, 23-30, 23-38, 23-39, 23-47 to 23-50, 23-55, 23-61
  - Demand volume, 16-3, 16-7, 16-11, 17-1, 17-7, 17-15, 17-16, 17-37, 18-6, 18-11, 18-25, 19-15, 19-19, 19-26, 19-59, 20-10, 20-12, 20-46, 21-11, 21-15, 22-14 to 22-16, 22-28, 23-7, 23-11, 23-29, 23-64, 23-69, 23-73, 23-83, 23-84, 23-92, 24-9, 24-30, 24-31
  - Density, 16-6, 18-15, 18-16, 18-19, 18-27 to 18-29, 18-82, 22-3, 23-2, 23-43, 23-44, 24-7, 24-13, 24-14, 24-19, 24-22, 24-24
  - Departure headway, 21-3 to 21-7, 21-9, 21-11, 21-14, 21-17 to 21-19, 21-26
  - Design analysis, 16-31, 18-79, 18-80, 19-29, 19-93, 20-46, 21-25, 22-28, 23-61, 24-11, 24-33, 24-34
  - Design hour, 23-61
  - Design speed, 23-26, 23-46, 23-56
  - Detection mode, 19-24, 19-40
  - Detection zone, 19-35, 19-39, 19-40
  - Detector, 17-4, 17-5, 17-11, 17-34, 19-4, 19-20, 19-39, 19-40, 19-56, 19-98, 23-63
  - Deterministic model, 17-34, 22-12, 22-13, 23-62
  - D-factor, 16-30, 19-92, 23-93
  - Diamond interchange, 20-10, 23-2, 23-5, 23-6, 23-10, 23-11, 23-13, 23-18 to 23-20, 23-22, 23-33, 23-42, 23-47, 23-50, 23-56, 23-61, 23-63, 23-64
  - Directional distribution, 17-15, 17-38, 24-16, 24-18, 24-31 to 24-33
  - Directional flow rate, 24-18
  - Directional split, 24-5, 24-15, 24-31
  - Displaced left turn intersection (DLT), 23-5, 23-6, 23-9 to 23-11, 23-17, 23-65, 23-68, 23-69, 23-71, 23-73, 23-81 to 23-86, 23-89 to 23-92, 23-94
  - Distributed intersection, 23-1, 23-2, 23-7, 23-9, 23-10 to 23-13
  - Diverge, 23-66, 23-67, 23-75
  - Diverging diamond interchange (DDI), 23-2, 23-5, 23-6, 23-8 to 23-11, 23-16, 23-19, 23-20, 23-22, 23-26, 23-32, 23-33, 23-36 to 23-39, 23-42 to 23-47, 23-50 to 23-54, 23-56 to 23-61
  - Divided median type, 18-60
  - Driver population, 20-4
  - Dual entry, 19-23, 19-37
  - Dwell time, 17-11, 18-67, 16-68, 18-73
  - Dynamic speed limit, 17-5
- ## E
- Effective green time, 18-32, 18-36, 18-73, 19-9, 19-11, 19-13, 19-27, 19-38, 19-49, 19-51, 19-52, 19-64, 19-89, 23-39, 23-44, 23-53 to 23-56, 23-59
  - Effective red time, 19-9, 19-11, 19-64, 19-74, 23-54
  - Effective walk time, 19-78, 19-79, 19-81
  - Effective walkway width, 24-10
  - 85th percentile speed, 19-73, 19-74, 19-85
  - Empirical model, 23-35, 23-62
  - Entry flow, 22-2, 22-3, 22-8, 22-17, 22-18, 22-29
  - Excess wait time, 18-67, 18-68, 18-76, 18-77
  - Exclusive off-street bicycle path, 24-1
  - Exclusive turn lane, 18-14, 18-17, 19-7, 19-21, 19-22, 19-24, 19-33, 19-40, 19-43
  - Exit flow, 18-24
  - Experienced travel time, 23-2, 23-12, 23-13, 23-26, 23-50, 23-70, 23-80, 23-84
  - Extension of effective green, 19-11, 19-12, 19-14, 23-39
  - Extra distance travel time, 23-12, 23-13, 23-15 to 23-17, 23-26, 23-56, 23-70, 23-75, 23-76, 23-79, 23-80

**F**

Facility, Chapter 16, Chapter 17, 18-2, 18-39, 18-41, 18-42, 18-48, 18-58, 18-67, 18-79, 18-82, 19-70, 20-6, 20-7, 20-11, 20-37, 21-10, 22-5, 22-14, 23-2, 23-5, 23-7, 23-8, 23-12, 23-13, 23-19, 23-20, 23-24, 23-61, 23-64, 23-80, 23-91, 24-3, 24-6 to 24-11, 24-13, 24-14, 24-16, 24-17, 24-19, 24-25, 24-29, 24-33, 24-34

Fixed-object effective width, 18-49, 24-10

Flared approach, 20-3, 20-8, 20-10, 20-46

Flow profile, 18-33, 19-9, 19-27, 19-49, 23-3, 23-76, 23-77, 23-82, 23-84 to 23-86

Flow rate, 16-11, 17-26, 17-44, 18-11, 18-14 to 18-17, 18-30, 18-33, 18-34, 18-44, 18-45, 18-50, 18-59, 18-80, 19-9, 19-12, 19-19, 19-22 to 19-27, 19-30 to 19-32, 19-41, 19-44 to 19-46, 19-48, 19-56, 19-58 to 19-60, 19-63 to 19-65, 19-67, 19-73, 19-74, 19-78, 19-80 to 19-82, 19-85, 19-87, 19-89, 19-90, 19-94, 20-13, 20-16, 20-20, 20-22, 20-24, 20-25, 20-27 to 20-30, 20-32, 20-38, 20-40, 20-41, 20-47, 21-3, 21-7, 21-11, 21-12, 21-14, 21-17, 21-19, 21-20, 22-8, 22-12, 22-16 to 22-22, 22-24, 22-27, 23-2, 23-7, 23-9, 23-10, 23-17, 23-29, 23-32, 23-37, 23-52, 23-54, 23-55, 23-58, 23-59, 23-73, 23-77, 23-78, 24-4, 24-12 to 24-14, 24-18, 24-20, 24-24, 24-25, 24-33, 24-34

Flow ratio, 19-44, 19-51, 19-58 to 19-62

Follow-up headway, 20-3, 20-4, 20-5, 20-7, 20-10, 20-18, 20-19, 20-20, 20-21, 22-3, 22-25, 23-52 to 23-54

Force-off, 19-5, 19-37, 19-39

Four-phase pattern, 21-2 to 21-4

Free-flow speed (FFS), 16-7, 16-14 to 16-16, 17-9, 17-12, 17-27, 17-28, 17-35, 17-36, 17-44, 18-3, 18-6, 18-7, 18-13, 18-27 to 18-29, 18-30, 18-31, 18-38, 18-82, 20-30, 23-29, 23-43, 23-44, 23-46, 23-59, 23-71, 23-79, 23-82, 23-93

Free-flow travel time, 23-14, 23-82

Freeway, 16-6, 17-13, 17-42, 19-31, 22-11, 23-1, 23-2, 23-4, 23-5, 23-8, 23-14 to 23-16, 23-19, 23-20, 23-22, 23-24, 23-26, 23-27, 23-33, 23-44, 23-45, 23-47, 23-50, 23-60, 23-64

Freeway facility, 23-2, 23-60

Freight, 17-35, 17-45

Full stop, 16-16, 18-36 to 18-38

Fully actuated control, 19-4, 19-56, 19-76, 19-88

**G**

Gap, 18-51, 18-54, 18-68, 18-70, 19-7, 19-13, 19-21, 19-23, 19-37, 19-38, 20-2 to 20-6, 20-8, 20-9, 20-12, 20-13, 20-15, 20-19, 20-22 to 20-24, 20-35, 20-40 to 20-43, 20-45, 20-47, 20-49, 22-2, 22-5, 22-11 to 22-13, 23-51 to 23-54, 23-58

Gap acceptance, 20-1, 20-2, 20-4, 20-8, 20-9, 20-19, 22-2, 22-5, 22-12, 22-13, 23-51 to 23-54, 23-58

Generalized service volume table, 16-30, 19-92

Geometric condition, 16-31, 18-79, 18-80, 19-93, 20-11, 20-37, 20-45, 20-46, 21-7, 22-27

Geometric delay, 18-34, 18-35, 23-79

Green time, 17-5, 19-9, 19-38, 19-48, 23-6, 23-7, 23-29, 23-39, 23-44, 23-47, 23-55, 23-82

**H**

Headway, 17-44, 18-29, 18-68, 18-75, 18-78, 19-10, 19-11, 19-13, 19-47, 19-97, 20-5, 20-18, 20-19, 20-39 to 20-41, 20-43, 20-45, 21-3 to 21-6, 21-8, 21-9, 21-13, 21-14, 21-16, 21-17, 22-3, 22-5, 23-2, 23-32, 23-43, 23-51, 23-63, 23-77, 23-97

Heavy vehicle, 18-59, 18-63, 18-64, 19-12, 19-23, 19-25, 19-30, 19-45, 19-46, 19-92, 20-11, 20-18, 20-19, 20-46, 21-4, 21-10, 21-13, 22-4, 22-6, 22-8, 22-14, 22-16, 22-22, 22-25, 22-28, 23-29, 23-31, 23-95

Hindrance, 24-15, 24-16

**I**

Impedance, 20-14, 20-16, 20-21, 20-24, 20-26, 20-33 to 20-36, 20-49, 22-20, 22-22

Incident, 17-1, 17-7, 17-8, 17-11 to 17-14, 17-18 to 17-23, 17-26, 17-30 to 17-33, 17-36, 17-38, 17-39, 17-41, 17-43, 17-44, 20-30, 21-18

Incident clearance time, 17-20

Incident detection time, 17-19, 17-20

Incident response time, 17-19, 17-20

Incremental delay, 19-50 to 19-53, 19-90, 19-95

Influence area, 16-10, 18-4, 18-10, 19-14, 19-18

Initial queue, 16-11, 17-27, 18-11, 19-2, 19-18, 19-19, 19-23, 19-29, 19-30, 19-50, 19-51, 19-53, 19-56, 19-65, 19-67 to 19-69, 19-90, 19-94, 23-48

Initial queue delay, 19-2, 19-50, 19-51, 19-53, 19-65, 19-69, 19-90

Inputs, 17-7, 17-12, 17-23, 17-38, 20-21, 22-12, 23-6, 23-61, 23-62, 23-71, 23-91, 23-97, 24-2, 24-25, 24-30, 24-34

Intelligent transportation system (ITS), 19-34, 19-99

Interchange, 16-6, 16-12, 16-15, 16-17, 16-22, 18-1, 18-12, 18-13, 18-23, 18-42, 18-43, 18-57, 18-58, 19-99, 20-10, 22-1, Chapter 23  
 Interchange ramp terminal, 16-15, 16-17, 16-22, 18-13, 18-23, 18-42, 18-43, 18-57, 18-58, 22-1, 23-1, 23-6, 23-19, 23-24, 23-28, 23-30, 23-31, 23-39, 23-49, 23-63  
 Internal link, 23-10, 23-35, 23-42, 23-43, 23-47 to 23-49  
 Interrupted flow, 20-11  
 Intersection delay, 19-24, 19-32  
 Interval, 16-5, 17-39, 17-40, 18-5, 18-34, 19-4, 19-9, 19-11, 19-13, 19-14, 19-23, 19-28, 19-29, 19-35 to 19-39, 19-51, 19-52, 19-63 to 19-65, 19-73, 19-76, 22-11, 23-40, 23-41, 23-47 to 23-49, 23-57 to 23-59, 24-13  
 Island, 19-73, 19-74, 19-84, 19-85, 20-13, 20-16, 20-17, 20-39, 22-1, 23-24, 23-26  
 Isolated intersection, 16-5, 16-12, 18-13, 19-29, 19-94, 20-3, 21-1

## J

Jam density, 23-43  
 Jughandle, 23-65, 23-87

## K

K-factor, 16-30

## L

Lane 1, 21-14, 21-15, 21-20  
 Lane 2, 21-14, 21-15, 21-20  
 Lane addition, 19-31  
 Lane distribution, 20-14, 20-19, 20-37, 23-33, 23-62, 23-63, 23-74  
 Lane group, 16-14, 18-13, 18-23, 18-42, 18-43, 18-57, 18-58, 19-12, 19-15, 19-21, 19-24, 19-40 to 19-56, 19-58, 19-59, 19-61 to 19-65, 19-67 to 19-69, 19-96, 23-3, 23-16, 23-29, 23-31, 23-33 to 23-35, 23-38, 23-55, 23-73, 23-80, 23-81, 23-87  
 Lane group delay, 19-54  
 Lane utilization, 17-36, 19-23, 19-30, 19-31, 19-45, 19-47, 22-14, 22-18, 22-19, 23-3, 23-5, 23-8 to 23-10, 23-22, 23-27, 23-30, 23-32 to 23-36, 23-49, 23-62, 23-63, 23-73, 23-74, 23-81  
 Lane width, 18-44, 18-45, 18-59, 19-23, 19-30, 19-31, 19-45, 19-47, 22-11, 23-29, 23-31

Level of service (LOS), 16-1 to 16-4, 16-6 to 16-9, 16-12, 16-14 to 16-28, 16-30, 16-31, 17-1, 17-7, 17-30, 17-40, 17-42, 17-43, 18-1, 18-2, 18-4, 18-6 to 18-9, 18-13, 18-38 to 18-42, 18-44, 18-48, 18-51 to 18-54, 18-56 to 18-59, 18-61 to 18-67, 18-70, 18-71, 18-78 to 18-80, 18-82, 19-1, 19-2, 19-4, 19-14 to 19-17, 19-20, 19-41, 19-44, 19-54, 19-55, 19-70, 19-76, 19-81, 19-84 to 19-86, 19-88, 19-90 to 19-95, 20-1, 20-2, 20-6, 20-7, 20-9, 20-32, 20-37, 20-39, 20-44 to 20-47, 21-1, 21-9, 21-11, 21-18, 21-19, 21-22, 21-25, 21-26, 22-1, 22-9, 22-10, 22-12, 22-23, 22-28, 23-2, 23-6, 23-10, 23-12 to 23-14, 23-16 to 23-18, 23-27, 23-28, 23-55, 23-56, 23-60 to 23-62, 23-70, 23-78, 23-80, 23-83, 23-88, 23-89, 23-93, 23-94, 24-1, 24-3 to 24-7, 24-9, 24-12 to 24-18, 24-25 to 24-34

Level-of-service score (LOS score), 16-1, 16-8, 16-17 to 16-28, 18-1, 18-7, 18-8, 18-41, 18-42, 18-44, 18-48, 18-51 to 18-54, 18-56, 18-58, 18-59, 18-61 to 18-67, 18-70, 18-71, 18-78, 19-1, 19-70, 19-84 to 19-86, 19-90, 19-91, 23-89, 24-17

Limited priority, 22-2, 22-3

Link, 16-3, 16-6, 16-7, 16-17, 16-20, 16-22, 16-24, 17-41, 18-4 to 18-8, 18-13, 18-19, 18-20, 18-28, 18-39, 18-41, 18-42, 18-45, 18-47 to 18-49, 18-52 to 18-54, 18-56 to 18-58, 18-61, 18-63, 18-64, 18-67, 18-70, 18-72, 18-73, 18-78, 23-2, 23-6, 23-10, 23-12 to 23-14, 23-16 to 23-18, 23-27, 23-28, 23-55, 23-56, 23-60 to 23-62, 23-70, 23-78, 23-80, 23-83, 23-88, 23-89, 23-93, 23-94

Link length, 18-19, 18-20, 18-28, 18-45, 23-43

Load factor, 18-67, 18-69, 18-77

Local street, 16-9, 16-12, 18-9, 22-29

Loop ramp, 23-5, 23-6, 23-22, 23-23, 23-56

Lost time, 18-32, 18-82, 19-9 to 19-12, 19-38, 19-58 to 19-60, 19-62, 19-92, 23-2, 23-7, 23-8, 23-10, 23-11, 23-30, 23-38 to 23-45, 23-47 to 23-50, 23-55, 23-56

## M

Macroscopic model, 22-13

Mainline, 23-23, 23-65

Major street, 16-2, 16-14, 17-2, 18-2, 18-21, 19-2, 19-8, 19-59, 19-61, 19-71, 19-78, 19-80, 19-82 to 19-85, 20-1, 20-3 to 20-7, 20-12 to 20-21, 20-23, 20-24, 20-30, 20-31, 20-33, 20-34, 20-37, 20-38, 20-40, 20-42, 20-45, 20-47, 21-22, 22-29, 23-9, 23-13, 23-65, 23-71, 23-74 to 23-79, 23-81, 23-87 to 23-89, 23-91

Maximum green, 19-13, 19-23, 19-35, 19-52, 19-56

Maximum recall, 19-37

Median, 17-27, 18-15, 18-19, 18-27, 18-28, 18-59, 18-60, 18-82, 19-36, 19-75, 20-10, 20-15, 20-18, 20-19, 20-25, 20-27, 20-37 to 20-39, 20-46, 23-2, 23-5, 23-11, 23-65, 23-66, 23-71, 23-73, 23-78

Median U-turn intersection (MUT), 23-2, 23-5, 23-6, 23-8 to 23-11, 23-65 to 23-67, 23-71, 23-73, 23-74, 23-76 to 23-81, 23-87, 23-89, 23-91, 23-94, 23-97

Meeting, 17-10, 17-40, 17-45, 19-98, 20-50, 22-30, 23-97, 24-3, 24-5 to 24-7, 24-15 to 24-17, 24-20, 24-21, 24-25, 24-29, 24-31

Merge, 20-13, 21-3, 22-8, 23-5, 23-11, 23-22, 23-66 to 23-68, 23-73, 23-75, 23-77 to 23-79, 23-85, 23-91, 23-93, 23-95

Minimum green, 19-23, 19-35 to 19-37, 19-40, 19-56, 23-29

Minimum recall, 19-37

Minor movement, 19-4, 19-5, 20-3, 20-4, 20-6, 20-13, 20-20, 20-30, 20-32, 20-33

Minor street, 19-7 to 19-9, 19-59, 19-61, 19-71, 19-79, 19-80, 19-84, 20-1, 20-4 to 20-6, 20-10, 20-12, 20-13, 20-16, 20-18, 20-19, 20-21, 20-33, 20-47, 21-22, 22-29, 23-9, 23-13, 23-71, 23-74 to 23-77, 23-85, 23-88, 23-93, 23-94

Mobility, 16-7, 16-10, 16-12, 17-13, 18-6, 18-10, 23-1, 24-7

Mode, 16-1, 16-3, 16-4, 16-6 to 16-8, 17-6, 17-30, 17-40, 17-41, 17-43, 18-1, 18-6 to 18-8, 18-41, 19-1, 19-4, 19-7, 19-8, 19-14 to 19-16, 19-21, 19-23, 19-24, 19-34 to 19-40, 19-64, 19-74, 19-75, 19-98, 20-6, 20-37, 20-45, 20-46, 21-9, 21-11, 21-22, 21-24, 21-25, 22-9, 22-26 to 22-29, 23-1, 23-28, 24-1, 24-9, 24-15, 24-17 to 24-25, 24-32, 24-33

Mode group, 24-17, 24-19, 24-21

Model, 17-37, 17-38, 17-41, 17-43, 17-44, 18-4, 18-12, 18-14, 18-22, 18-27, 18-33, 18-34, 18-36, 18-39, 18-80, 18-81, 19-22, 19-40, 19-62, 19-94, 20-1, 20-3, 20-4, 20-8 to 20-10, 20-19, 20-38, 20-45, 21-5 to 21-8, 21-27, 22-1 to 22-5, 22-11 to 22-13, 22-20 to 22-23, 22-25 to 22-27, 23-28, 23-33 to 23-37, 23-43, 23-44, 23-49, 23-52, 23-53, 23-63, 23-70, 24-17, 24-23, 24-34

Monte Carlo method, 17-38

Motorized vehicle mode, 16-4, 16-6, 16-7, 18-6, 18-7, 18-22, 18-59, 18-60, 19-14, 19-16, 19-73 to 19-76, 19-87, 19-88, 20-1, 20-3, 20-11, 20-21, 20-37

Movement capacity, 16-14, 18-21, 18-25, 18-32, 18-39, 20-3, 20-11, 20-21, 20-22, 20-24, 20-25, 20-27, 20-28, 20-33 to 20-35, 20-47

Movement group, 16-13, 18-13 to 18-15, 18-21, 19-21, 19-22, 19-24, 19-26 to 19-34, 19-42 to 19-44, 19-46, 19-67, 23-73

Move-up time, 20-30, 21-3, 21-18

Multilane roundabout, 22-1, 22-5, 22-7, 22-19, 22-28

Multimodal, 16-1, 16-3, 16-4, 16-29, 16-33, 18-1, 18-42, 18-58, 18-83, 19-1, 19-98, 24-35

## N

Near-side stop, 18-72, 18-73

Node, 23-11, 23-24, 23-63, 23-71

Nonrestrictive median, 18-60

## O

Off-line bus stop, 18-71

Off-ramp, 23-16, 23-20, 23-42 to 23-46

Offset, 17-4, 18-32, 19-24, 19-38, 23-6, 23-9, 23-11, 23-29, 23-76, 23-82, 23-83, 24-28

Off-street, 16-19, 16-24, 18-48, 18-61, 24-1 to 24-3, 24-5 to 24-7, 24-10, 24-11, 24-14, 24-15, 24-17, 24-25, 24-30, 24-34

One-stage gap acceptance, 20-15

On-ramp, 19-31, 23-64

On-time arrival, 17-10

Operational analysis, 16-13, 16-29 to 16-31, 17-14, 18-20, 18-79, 18-80, 19-79, 19-92, 19-93, 20-46, 21-25, 22-28, 22-29, 23-6, 23-26, 23-28, 23-30, 23-61, 23-62, 23-66, 23-70, 23-71, 23-88, 23-89, 23-94, 23-95, 24-11, 24-33

Opposing approach, 19-9, 19-63, 21-2, 21-3, 21-7 to 21-9, 21-14, 21-20, 21-26, 23-69

Outputs, 17-43, 20-46, 21-25, 22-28, 23-28, 23-61, 24-34

Overflow queue, 18-36, 19-52, 19-69

## P

Partial cloverleaf interchange (parclo), 23-10, 23-11, 23-15, 23-19, 23-20, 23-22, 23-23, 23-26, 23-34, 23-35, 23-61

Partial diamond interchange, 23-20

Passage time, 19-20, 19-23, 19-35, 19-52, 19-56, 23-29

Passenger car, 16-29, 19-30, 19-46, 21-4, 22-7, 22-16, 22-17, 23-42

Passenger-car equivalent (PCE), 22-21, 22-22

Passenger service time, 18-74

Passenger trip length, 18-67, 18-69, 18-77, 18-78

Pavement condition rating, 18-60, 18-63

Peak hour, 16-11, 16-29, 16-30, 17-7, 17-35, 17-41, 17-44, 18-11, 18-16, 18-17, 19-19, 19-23 to 19-26, 19-92, 20-2, 20-10 to 20-12, 20-46, 20-47, 21-10, 21-11, 21-25, 22-14 to 22-16, 22-28, 23-2, 23-29, 23-73, 23-95, 24-2, 24-9, 24-12, 24-16, 24-18, 24-24, 24-25

- Peak hour factor (PHF), 16-11, 16-29, 16-30, 17-35, 17-44, 18-11, 18-16, 18-17, 19-19, 19-23 to 19-26, 19-92, 20-2, 20-10 to 20-12, 20-46, 21-10, 21-11, 21-25, 22-14 to 22-16, 22-28, 23-2, 23-29, 23-73, 23-95, 24-2, 24-8, 24-9, 24-12, 24-16, 24-18, 24-24, 24-25, 24-30 to 24-33
- Pedestrian, 16-2 to 16-4, 16-6, 16-8, 16-9, 16-17 to 16-21, 16-24, 17-5, 17-34, 17-35, 18-2, 18-4 to 18-9, 18-31, 18-32, 18-38, 18-41 to 18-56, 18-59 to 18-61, 18-67, 18-70, 18-78, 18-83, 19-2, 19-5 to 19-7, 19-9, 19-14, 19-16, 19-17, 19-23, 19-25, 19-31, 19-36, 19-37, 19-40, 19-44, 19-45, 19-47, 19-48, 19-70 to 19-85, 19-88, 19-90, 19-98, 19-99, 20-3 to 20-6, 20-13, 20-15, 20-21, 20-33 to 20-46, 20-50, 21-10, 21-22, 21-23, 22-7, 22-8, 22-10, 22-11, 22-20 to 22-22, 22-26, 22-27, 22-29, 22-31, 23-19, 23-22, 23-28, 23-29, 23-32, 23-50, 23-60, 23-65, 23-88 to 23-90, Chapter 24
- Pedestrian circulation route, 24-27
- Pedestrian clear interval, 19-36, 19-37, 19-75, 19-78, 19-79, 19-81
- Pedestrian flow rate, 18-44, 18-49, 18-50, 19-23, 19-31, 19-73, 19-74, 19-83, 20-13, 20-38, 20-40, 23-29, 24-12, 24-13, 24-28
- Pedestrian mode, 16-6, 18-6, 18-8, 18-59, 18-60, 19-77, 22-26, 24-9
- Pedestrian plaza, 24-6, 24-13, 24-27
- Pedestrian recall, 19-37
- Pedestrian service time, 19-82
- Pedestrian space, 16-1, 16-6, 16-8, 16-17 to 16-21, 18-1, 18-6, 18-7, 18-41, 18-42, 18-49, 18-51, 18-56, 19-70, 24-3, 24-6, 24-13, 24-14, 24-30
- Pedestrian start-up time, 20-38, 20-39
- Pedestrian street, 24-1, 24-3, 24-13
- Pedestrian walkway, 24-1, 24-27, 24-28, 24-33
- Pedestrian zone, 24-3, 24-13, 24-28
- Performance measure, 16-1, 16-2, 16-6 to 16-9, 16-12 to 16-14, 16-17, 16-18, 16-21 to 16-23, 16-25, 16-26, 16-28, 16-31, 17-1, 17-3, 17-7 to 17-9, 17-15, 17-25, 17-27, 17-38 to 17-42, 18-1, 18-3, 18-5 to 18-7, 18-13, 18-20, 18-23, 18-38, 18-39, 18-41, 18-42, 18-47, 18-56, 18-58, 18-60, 18-66, 18-70, 18-71, 18-75, 18-78, 18-79, 18-81, 19-1, 19-3, 19-14, 19-16, 19-20, 19-41, 19-55, 19-57, 19-70, 19-85, 19-86, 19-91, 19-93, 19-94, 19-95, 20-1, 20-7, 20-9, 20-37, 21-25, 22-1, 22-2, 22-10, 22-29, 23-6, 23-9, 23-10, 23-12, 23-18, 23-26, 23-28, 23-55, 23-61, 23-62, 23-70, 23-71, 23-86, 23-88, 23-89, 24-2, 24-6, 24-28, 24-30
- Permitted mode, 18-37, 19-7, 19-8, 19-74
- Permitted turn, 19-7, 19-94
- Phase, 16-30, 17-4, 17-35, 18-2, 18-12, 18-23, 18-32 to 18-34, 19-2, 19-4 to 19-13, 19-15, 19-20 to 19-24, 19-26, 19-27, 19-34 to 19-39, 19-41, 19-49 to 19-52, 19-55, 19-56, 19-58 to 19-63, 19-67, 19-68, 19-71 to 19-73, 19-75, 19-76, 19-78 to 19-81, 19-83, 19-86 to 19-88, 19-92, 19-94, 19-97, 21-1 to 21-4, 21-22 to 21-24, 23-7, 23-9, 23-17, 23-29, 23-39, 23-41, 23-42, 23-44, 23-45, 23-47, 23-48, 23-50, 23-53, 23-54, 23-57, 23-58, 23-61, 23-65, 23-68, 23-81 to 23-83, 23-90, 23-92
- Phase flow ratio, 19-59, 19-60, 19-62
- Phase lost time, 19-10 to 19-12, 19-60, 19-62
- Phase pair, 19-7, 19-59
- Phase pattern, 21-3
- Phase recall, 19-23
- Phase sequence, 19-4, 19-6, 19-8, 19-9, 19-23, 19-34, 19-37, 19-38, 19-56, 19-59 to 19-62, 19-94, 21-22
- Planning and preliminary engineering analysis, 16-6, 16-13, 16-31, 17-14, 18-5, 18-16, 18-17, 18-20, 18-24, 18-31, 18-80, 19-14, 19-24 to 19-26, 19-39, 19-79, 19-93, 20-46, 21-25, 22-28, 24-34
- Planning time index, 17-10
- Platoon, 16-2, 16-5, 16-18, 17-2, 17-4, 18-2, 18-4, 18-26, 18-32, 18-33, 18-43, 18-80, 18-81, 18-82, 19-2, 19-18, 19-23, 19-26 to 19-29, 19-63, 19-64, 19-82, 20-3, 20-7, 20-20, 20-21, 20-39, 20-40, 24-3, 24-4, 24-13, 24-14
- Platoon dispersion, 18-33, 18-80, 18-81
- Platoon ratio, 18-32, 19-23, 19-26 to 19-28, 19-64
- Point, 16-3, 16-6, 16-13, 16-30, 17-10, 17-23, 17-30, 17-34, 18-4 to 18-6, 18-14 to 18-19, 18-25 to 18-28, 18-30 to 18-33, 18-37, 18-43, 18-47, 18-54, 18-59, 18-64, 18-67, 18-68, 19-6, 19-22, 19-24, 19-28, 19-32 to 19-34, 19-37 to 19-39, 19-49, 19-55, 19-63, 19-73, 19-83, 19-87, 19-88, 19-94, 19-95, 20-29, 20-42, 21-26, 22-13, 24-2, 24-7, 24-10, 24-16, 24-20, 24-25, 24-27, 24-32
- Potential capacity, 20-3, 20-11, 20-19 to 20-22, 20-25, 20-33 to 20-35
- Precision, 16-4, 16-31, 17-7, 18-4, 18-80, 19-14, 19-93
- Preemption, 16-9, 17-11, 18-9, 19-16, 19-21
- Prepositioning, 19-30
- Presence detection, 19-23, 19-24
- Pretimed control, 17-35, 19-4, 19-34, 19-38, 19-41, 19-49, 19-92
- Prevailing condition, 19-11, 19-12, 19-41
- Priority reversal, 22-3, 22-10
- Progression, 16-7, 17-11, 18-6, 18-7, 18-12, 19-5, 19-15, 19-26 to 19-29, 19-38, 19-51, 19-56, 19-94, 19-98, 22-14, 23-7, 23-9, 23-42, 23-44, 23-74, 23-76, 23-82



**Q**

Quality of service, 16-1, 16-3, 16-8 to 16-10, 16-17, 16-19, 16-22, 16-24, 16-26, 18-1, 18-7 to 18-10, 18-41, 18-43, 18-53, 18-57, 18-58, 18-66, 18-68, 19-1, 19-16 to 19-18, 19-70, 19-71, 19-86, 22-9, 23-2, 23-60, 24-1, 24-3, 24-6, 24-7, 24-26, 24-31

Queue, 16-7, 16-10 to 16-12, 16-14, 16-29, 16-30, 16-32, 17-36, 18-2, 18-6, 18-10 to 18-12, 18-15, 18-21, 18-25 to 18-27, 18-30, 18-36, 18-37, 18-70, 18-71, 18-82, 19-2, 19-10 to 19-13, 19-15, 19-16, 19-18 to 19-20, 19-22, 19-29, 19-30, 19-35, 19-38, 19-40, 19-41, 19-49 to 19-56, 19-62 to 19-67, 19-69, 19-79, 19-98, 20-3, 20-7 to 20-11, 20-22 to 20-26, 20-28 to 20-32, 20-34, 20-35, 20-45 to 20-49, 21-3, 21-10, 21-19, 21-22, 21-24, 21-26, 21-27, 22-10 to 22-12, 22-23, 22-24, 22-29, 23-7, 23-9, 23-11, 23-12, 23-16, 23-27, 23-28, 23-30 to 23-32, 23-36, 23-38 to 23-44, 23-47 to 23-50, 23-52, 23-53, 23-55 to 23-59, 23-61, 23-62, 23-70, 23-78, 23-80, 23-82, 24-27

Queue accumulation polygon, 19-13, 19-62 to 19-64

Queue delay, 19-51, 20-9

Queue jump, 18-71

Queue length, 18-2, 19-2, 19-18, 19-41, 20-3, 20-7, 20-11, 20-28, 20-29, 20-32, 20-46, 20-48, 21-19, 22-10, 22-24, 22-29, 23-36, 23-41, 23-43, 23-50, 23-52, 23-57, 23-58, 23-62, 23-78

Queue spillback, 19-16, 19-20, 20-7, 21-10, 23-7, 23-12, 23-49, 23-61, 23-78

Queue storage ratio, 19-20, 19-54, 19-55, 23-27, 23-31, 23-55, 23-56

Queued state, 20-9

Queuing area, 24-1

**R**

Ramp, 16-6, 16-12, 17-43, 18-5, 18-12, 18-35, 19-99, 20-10, 22-11, 23-3, 23-5, 23-6, 23-10, 23-15, 23-19, 23-20, 23-22 to 23-28, 23-30, 23-33, 23-38 to 23-46, 23-48, 23-61, 23-62, 23-64, 23-87, 23-91, 23-96, 24-3, 24-13

Ramp meter, 17-43, 22-11, 23-27, 23-64

Rank, 20-4, 20-5, 20-13 to 20-16, 20-20 to 20-27, 20-30 to 20-36

Receiving lanes, 19-23, 19-33, 19-48, 21-8

Recreational vehicle (RV), 16-9, 18-9, 19-17

Recurring congestion, 17-33

Red clearance interval, 19-5, 19-9 to 19-13, 19-36 to 19-38, 19-79, 19-88, 23-45

Red time, 19-9, 19-11

Reentry delay, 18-67, 18-70 to 18-74

Reference phase, 19-24, 19-38, 23-82

Regression model, 20-1, 22-2, 22-3, 24-17, 24-25

Reliability rating, 17-10, 17-27

Reliability reporting period, 17-4, 17-7 to 17-9, 17-12 to 17-15, 17-18, 17-24 to 17-29, 17-31, 17-37 to 17-40

Residual queue, 16-11, 17-27, 18-11, 19-19, 19-30, 19-52, 19-55, 19-57, 19-69, 22-23, 23-12, 23-57, 23-58

Rest-in-walk mode, 19-21, 19-36, 19-75

Restricted crossing U-turn intersection (RCUT), 23-vii, 23-viii, 23-ix, 23-2, 23-5, 23-6, 23-8, 23-9, 23-10, 23-11, 23-12, 23-13, 23-65, 23-66, 23-67, 23-71, 23-73, 23-74, 23-75, 23-76, 23-77, 23-78, 23-79, 23-80, 23-81, 23-83, 23-87, 23-88, 23-89, 23-91, 23-93, 23-94, 23-95, 23-97

Restrictive median, 16-29, 16-30, 18-15, 18-19, 18-28

Right-of-way, 16-3, 16-9, 16-17, 16-22, 16-27, 18-4, 18-9, 18-41, 18-57, 18-66, 18-67, 19-5 to 19-7, 19-17, 19-40, 19-89, 19-90, 20-4, 20-5, 20-9, 21-2 to 21-4, 22-20, 22-26

Right-turn-on-red, 18-82, 19-20, 19-23, 19-25, 19-44, 19-73, 19-81, 19-85, 19-96, 23-1, 23-6, 23-20, 23-28, 23-62, 23-68, 23-29, 23-72, 23-94, 23-97

Ring, 19-6, 19-7, 19-37, 19-58 to 19-62

Roundabout, 16-9, 16-15, 16-17, 16-22, 16-29, 16-30, 16-32, 18-8, 18-14, 18-22, 18-23, 18-34, 18-35, 18-42, 18-43, 18-57, 18-58, 18-67, 18-71 to 18-73, 18-82, 21-26, Chapter 22, 23-2, 23-7, 23-18 to 23-20, 23-22, 23-24, 23-26, 23-27, 23-50, 23-52, 23-55, 23-57, 23-61, 23-62, 23-74

Running speed, 16-16, 16-24, 16-27, 17-26, 18-30, 18-32, 18-44, 18-47, 18-52, 18-53, 18-59, 18-61 to 18-64, 18-72 to 18-75, 18-81, 19-10

Running time, 16-7, 16-14, 16-23, 16-27, 17-27, 17-35, 17-36, 18-6, 18-21, 18-27, 18-29 to 18-33, 18-38, 18-47, 18-61, 18-62, 18-67, 18-70 to 18-72, 18-74, 18-75

Rural, 17-10, 18-19, 19-55, 21-22, 21-26, 22-26, 23-20, 23-66

**S**

Saturation flow rate, 17-26, 17-44, 18-13, 18-36, 18-37, 18-80, 18-82, 19-3, 19-9, 19-11 to 19-13, 19-30, 19-41, 19-44 to 19-49, 19-58, 19-59, 19-63, 19-64, 19-67, 19-89, 19-94, 19-96, 20-5, 20-10, 20-24, 22-3, 23-3, 23-9 to 23-11, 23-22, 23-27, 23-31 to 23-33, 23-35, 23-37, 23-51, 23-54, 23-55, 23-58, 23-59, 23-63, 23-72, 23-77, 23-78, 23-82, 23-87

Saturation headway, 19-10, 19-11, 19-40, 21-3, 21-5 to 21-8, 21-10, 21-11, 21-13, 21-16, 21-17, 21-20, 21-21, 23-47, 23-48, 23-54, 23-63

- Scenario, 17-3, 17-7, 17-8, 17-13, 17-14, 17-24 to 17-27, 17-31, 17-32, 17-35, 17-36, 17-39 to 17-41, 17-43, 19-26, 19-57, 20-7, 20-12, 20-15, 20-43, 21-10, 21-11, 21-22, 22-16, 23-82, 24-23
- Scenario generation, 17-8, 17-14, 17-26
- Section, 17-3, 17-29, 24-11, 24-22
- Segment, 16-3, 16-5 to 16-10, 16-12 to 16-29, 16-32, 17-9, 17-12, 17-18, 17-20 to 17-27, 17-29, 17-37, Chapter 18, 19-20, 19-28, 19-29, 19-33, 19-38, 19-49, 19-81, 19-96, 20-9, 20-46, 21-25, 22-28, 23-7, 24-2, 24-3, 24-6, 24-9, 24-13, 24-19 to 24-21
- Segment delay, 19-96, 20-9
- Semiautomated control, 19-4, 19-5
- Sensitivity analysis, 22-24
- Service flow rate, 24-5
- Service measure, 16-2, 16-3, 18-1, 18-4, 19-2, 19-4, 20-39, 20-44, 22-9, 23-1, 23-12, 24-3, 24-8, 24-9, 24-13, 24-14
- Service time, 18-71, 19-13, 19-24, 19-41, 19-44, 19-82, 21-3, 21-5, 21-6, 21-8, 21-11, 21-14, 21-18
- Service volume, 18-79, 19-92, 24-33, 24-34
- Severe weather, 17-26, 17-31
- Shared lane, 16-13, 18-17, 18-35, 19-21, 19-24, 19-27, 19-33, 19-41, 19-43, 19-44, 19-47, 19-63, 19-67, 19-94, 20-3, 20-22 to 20-24, 20-28 to 20-31, 20-47, 23-36, 23-73
- Shared-lane capacity, 20-22, 20-28
- Shared-use path, 24-1, 24-2, 24-6 to 24-8, 24-14 to 24-17, 24-21, 24-23, 24-30, 24-31, 24-34
- Shock wave, 23-43, 23-44
- Short length, 18-12
- Shoulder, 16-6, 17-11 to 17-13, 17-20 to 17-22, 17-26, 18-44 to 18-46, 18-52, 18-53, 18-59, 18-60, 18-64, 19-31, 19-87 to 19-89, 19-91
- Shy distance, 18-49, 18-50, 24-10, 24-12
- Side street, 19-29, 23-8, 23-65, 23-82, 23-87, 23-91, 23-92
- Sidepath, 24-1
- Sidewalk, 16-8, 16-17 to 16-21, 18-4, 18-7, 18-41 to 18-44, 18-46 to 18-50, 18-52, 18-53, 18-56, 19-70, 19-71, 19-75 to 19-77, 19-80, 19-81, 19-88, 23-60, 24-1, 24-6, 24-10 to 24-12, 24-27, 24-28
- Simulation, 17-43, 17-44, 18-81, 18-82, 19-32, 19-94 to 19-96, 20-8 to 20-10, 20-37, 20-38, 22-10, 22-13, 22-31, 23-27, 23-28, 23-50, 23-59, 23-61 to 23-63, 23-70, 24-34
- Single entry, 19-23, 19-37, 22-4
- Single-lane roundabout, 22-1, 22-4, 22-5, 22-28
- Single-point urban interchange (SPUI), 23-2, 23-5, 23-10, 23-11, 23-19, 23-20, 23-23, 23-26, 23-30, 23-31, 23-33, 23-61
- Space, 16-3, 16-8, 16-18 to 16-21, 18-7, 18-8, 18-22, 18-41 to 18-43, 18-49, 18-51, 18-56, 19-32, 19-46, 19-55, 19-71, 19-75, 19-77, 19-79 to 19-81, 19-83, 20-31, 23-27, 23-41, 23-44, 23-78, 24-4, 24-10, 24-13, 24-14, 24-27, 24-28, 24-30, 24-31, 24-35
- Space mean speed, 17-10
- Spacing, 16-5, 16-30, 18-15, 18-27, 18-29, 18-44, 18-46, 18-53, 19-28, 23-1, 23-5, 23-7, 23-20, 23-42, 23-43, 24-11, 24-28
- Spatial stop rate, 16-16, 17-9, 18-38, 18-39
- Special event, 17-4, 17-7 to 17-9, 17-12, 17-18, 17-22 to 17-25, 17-37, 19-49, 24-3, 24-27
- Speed, 16-1, 16-4, 16-6 to 16-8, 16-12, 16-14 to 16-16, 16-18 to 16-20, 16-23, 16-24, 16-27, 16-29, 16-30, 17-1, 17-4, 17-5, 17-9, 17-10, 17-24, 17-26, 17-28, 17-30, 17-34 to 17-36, 17-43, 17-44, 18-1, 18-6, 18-7, 18-15, 18-19, 18-20, 18-27 to 18-32, 18-36, 18-38, 18-43, 18-47 to 18-53, 18-55, 18-60 to 18-63, 18-68, 18-71, 18-72, 18-75, 18-77, 18-80 to 18-82, 19-5, 19-11, 19-12, 19-16, 19-23, 19-24, 19-35, 19-36, 19-38 to 19-40, 19-71, 19-73, 19-74, 19-81, 19-84, 20-30, 20-33, 20-38, 20-39, 22-8, 22-26, 23-2, 23-12, 23-27, 23-29, 23-32, 23-43, 23-44, 23-46, 23-66, 23-77, 23-78, 23-90, 23-93, 24-4, 24-7 to 24-9, 24-13, 24-15 to 24-17, 24-19, 24-20, 24-28, 24-30 to 24-33
- Speed adjustment factor (SAF), 18-52, 18-63, 19-84
- Speed harmonization, 17-36
- Spillback, 16-2, 16-12, 17-2, 18-2, 18-12, 18-24, 18-26, 18-27, 19-2, 19-49, 23-7, 23-24, 23-27, 23-49
- Spillover, 23-12, 23-27, 24-7, 24-11, 24-33
- Split, 17-4, 17-35, 19-8, 19-9, 19-24, 19-27, 19-34 to 19-36, 19-38, 19-39, 23-20, 23-83, 24-5, 24-9, 24-17, 24-18, 24-32, 24-33
- Split phasing, 19-8, 19-9, 19-27, 19-34
- Splitter island, 22-17
- Stairway, 24-6, 24-11, 24-13, 24-14, 24-28
- Start-up lost time, 18-32, 19-10 to 19-13, 19-22, 19-62, 19-96, 23-39, 23-44, 23-46, 23-63, 23-85
- Stochastic model, 22-12, 22-13
- Stop rate, 16-1, 16-12, 16-16, 17-27, 18-1, 18-13, 18-21, 18-36, 18-38
- Stop spacing, 18-69
- Stop-line detector length, 19-24, 19-39
- Stopped delay, 20-30
- Storage length, 18-18, 19-20, 19-33
- Street corner, 19-77
- Study period, 16-5, 16-10 to 16-12, 17-3, 17-7, 17-12 to 17-15, 17-25, 17-29, 17-38, 17-41, 18-4, 18-5, 18-10 to 18-12, 19-14, 19-18 to 19-20, 19-22, 19-73, 19-87
- Subject approach, 18-62, 19-27, 19-31, 19-47, 19-54, 19-88, 19-91, 20-15, 21-2 to 21-4, 21-6, 21-7, 21-17, 21-18, 21-26, 23-34

Sustained spillback, 16-2, 17-2, 18-2, 18-25, 18-27, 19-2, 19-45, 19-49  
 System, 16-6, 17-3, 17-4, 17-11, 17-13, 17-20, 17-34, 17-38, 17-40, 17-43, 17-45, 18-5, 18-22, 18-23, 18-35, 18-60, 18-68, 18-80, 19-5, 19-18, 19-27, 19-28, 19-34, 19-38 to 19-40, 19-56, 19-77, 19-94, 20-8, 20-10, 21-6, 22-13, 23-13, 23-27, 23-44, 23-49, 23-57, 23-58, 23-82, 23-83, 23-92, 23-96  
 System element, 19-77

## T

Temporal variability, 17-7  
 Three-level diamond interchange, 23-20  
 Through vehicles, 16-7, 16-14, 16-16, 17-9, 17-29, 18-6, 18-13, 18-14, 18-18 to 18-21, 18-26, 18-27, 18-30, 18-31, 18-34, 18-36, 18-38, 18-62, 18-74, 19-20, 19-22, 19-76, 19-88, 20-5, 20-6, 20-31, 21-3, 21-4, 23-6, 23-44, 23-65, 23-73, 23-74, 23-81  
 Throughput, 21-3, 21-7, 21-17, 23-63  
 Tight urban diamond interchange, 23-20  
 Time interval, 16-5, 16-13, 17-3, 17-14, 18-5, 18-20, 19-14, 19-39, 19-64, 20-5, 20-39  
 Time-space, 19-9, 19-77, 19-79 to 19-81, 19-83  
 Tool, 16-2, 16-23, 16-32, 17-2, 17-4, 17-34, 17-43, 17-44, 18-2, 18-12, 18-13, 18-27, 18-43, 18-58, 18-66, 18-80 to 18-82, 19-2, 19-20, 19-71, 19-86, 19-94 to 19-96, 20-8 to 20-10, 20-37, 20-38, 21-10, 22-10 to 22-13, 23-27, 23-28, 23-59, 23-62 to 23-64, 23-70, 23-81  
 Traffic analysis tool, 18-80, 19-94, 22-12, 23-28  
 Traffic circle, 22-10, 23-26  
 Traffic condition, 16-6, 16-9, 16-31, 18-4, 18-5, 18-9, 18-24, 18-79, 19-12, 19-14, 19-16, 19-45, 19-74, 19-93, 20-45, 21-2, 22-27, 23-32  
 Traffic control device, 16-7, 17-9, 17-30, 18-6, 18-12, 18-27, 18-30, 18-72, 19-11, 22-11, 23-71  
 Traffic pressure, 23-11, 23-32, 23-33  
 Transit frequency, 18-67, 18-69, 18-75, 18-76  
 Transit mode, 16-6, 16-8, 18-6 to 18-8  
 Transition, 17-11, 24-27  
 Travel demand model, 17-40  
 Travel mode, 16-1, 16-3, 16-6, 16-8, 16-10, 16-12, 16-17, 16-22, 16-26, 17-4, 18-1, 18-7, 18-8, 18-10, 18-13, 18-41, 18-42, 18-57, 18-58, 18-66, 19-1, 19-16, 19-18, 19-20, 19-70, 19-86, 24-3  
 Travel speed, 16-1, 16-7, 16-12 to 16-20, 16-22 to 16-24, 16-26 to 16-28, 17-5, 17-9, 17-27, 17-29, 18-1, 18-6, 18-7, 18-13, 18-38, 18-42, 18-51, 18-58, 18-62, 18-66, 18-69, 18-71, 18-75, 18-76, 18-81, 18-82, 20-42, 23-12, 24-5, 24-7

Travel time, 16-2, 16-14, 16-15, 16-19, 16-20, 16-23, 16-24, 16-27, 17-1, 17-3, 17-7 to 17-10, 17-15, 17-25, 17-27 to 17-29, 17-31, 17-40 to 17-43, 18-2, 18-34, 18-68, 18-73, 18-75, 18-76 to 18-78, 18-82, 19-11, 19-15, 19-24, 19-95, 21-7, 21-18, 23-1, 23-3, 23-12 to 23-15, 23-27, 23-62, 23-71, 23-77, 23-78, 23-82, 23-93, 24-20  
 Travel time distribution, 17-7, 17-15  
 Travel time index, 17-9, 17-28, 17-29  
 Travel time rate, 18-75 to 18-77  
 Travel time reliability, 16-2, Chapter 17, 18-2  
 Truck, 16-9, 16-10, 17-11, 18-9, 18-10, 19-12, 19-17, 19-18, 19-73, 20-14, 24-12  
 Turn bay spillback, 18-27  
 Turn lane, 16-16, 16-29, 16-30, 17-36, 18-15, 18-17, 18-18, 18-39, 18-40, 19-21, 19-25, 19-33, 19-43, 19-60 to 19-63, 19-67, 19-92, 20-10, 20-16, 20-17, 20-23, 20-24, 20-28, 22-19, 23-8, 23-29, 23-34, 23-35, 23-37, 23-38, 23-63, 23-66, 23-68, 23-74, 23-84, 23-85, 23-94  
 Turning movement, 19-95, 20-26, 20-46, 21-4, 21-5, 21-11, 21-25, 21-26, 22-14, 22-18, 22-28, 23-2, 23-5, 23-6, 23-8, 23-9, 23-11, 23-20, 23-22, 23-25, 23-26, 23-29, 23-31, 23-32, 23-34, 23-37, 23-48, 23-51, 23-57, 23-61 to 23-63, 23-68, 23-71, 23-73, 23-81, 23-82  
 Two-lane highway, 24-1, 24-6  
 Two-phase pattern, 21-3  
 Two-stage crossing, 20-15, 20-38 to 20-41, 20-44, 23-88  
 Two-stage gap acceptance, 20-3, 20-8, 20-15, 20-25, 20-27  
 Two-way left-turn lane (TWLTL), 18-18, 18-60, 19-33, 20-10  
 Two-way STOP-controlled (TWSC), 16-9, 16-17, 16-22, 16-32, 18-5, 18-8, 18-23, 18-42, 18-47, 18-57, 18-61, 18-72, 18-82, Chapter 20, 21-19, 21-22, 22-2, 23-3, 23-18, 23-26, 23-27, 23-51, 23-64

## U

Uncertainty, 20-6, 21-3, 22-2, 22-5  
 Uncontrolled, 16-14, 18-5, 18-6, 18-21, 18-32, 18-35, 18-36, 18-44, 18-47, 18-51, 18-54, 18-62, 19-11, 19-71, 20-1, 20-37  
 Uniform delay, 19-2, 19-50, 19-51, 19-53, 19-62, 19-64, 19-65, 19-67, 19-68, 19-95  
 Uninterrupted flow, 23-85  
 Unit extension, 19-35  
 Unmet demand, 19-51, 19-53, 19-65, 19-67 to 19-69  
 Unsignalized intersection, Chapter 20, Chapter 21, Chapter 22, 23-7, 23-19, 23-57

Urban, 16-1 to 16-3, 16-6 to 16-10, 16-12 to 16-15, 16-17, 16-19, 16-22, 16-23, 16-26, 16-27, 16-29, 16-30, 16-32, 16-33, 17-1, 17-2, 17-4 to 17-7, 17-9 to 17-14, 17-17, 17-18, 17-21, 17-24 to 17-28, 17-34, 17-35, 17-37, 17-42, 18-1 to 18-10, 18-12, 18-13, 18-19, 18-22 to 18-25, 18-28, 18-30, 18-32, 18-34, 18-39 to 18-41, 18-48, 18-57, 18-61, 18-66, 18-71, 18-79 to 18-83, 19-2, 19-17, 19-18, 19-27, 19-49, 19-77, 19-88, 19-98, 19-99, 20-7, 20-10, 20-20, 20-46, 20-47, 20-49, 20-50, 21-22, 22-8, 22-13, 22-26, 23-3, 23-6, 23-11, 23-12, 23-20, 23-23, 23-52, 23-57, 23-59, 23-60, 23-66, 23-71, 23-79, 23-81, 23-82, 23-84, 23-97, 24-6, 24-10, 24-35

Urban street, Chapter 16, Chapter 17, Chapter 18, 19-17, 19-27, 19-49, 19-88, 20-7, 20-20, 20-46, 23-12, 23-52, 23-57, 23-59, 23-60, 23-81, 24-6, 24-10

Urban street facility, Chapter 16, 17-2, 17-7, 17-9 to 17-12, 17-14, 17-24, 17-27, 17-28, 18-2, 18-79, 19-49, 23-59, 23-60

Urban street segment, 16-2, 16-6, 17-2, Chapter 18, 19-27, 19-49, 20-7, 20-20, 20-46, 23-12

U-turn, 20-4, 20-12, 20-14, 20-15, 20-18, 20-19, 20-21 to 20-23, 20-25, 20-27, 20-34, 20-46, 22-19, 23-5, 23-6, 23-8 to 23-11, 23-20, 23-24, 23-65 to 23-67, 23-70 to 23-80, 23-87, 23-89, 23-91, 23-93, 23-94

## V

Validation, 23-70, 23-96

Variability, 17-1, 17-7 to 17-10, 17-27, 17-38, 18-35, 24-2

Volume, 16-3, 16-4, 16-6 to 16-8, 16-11, 16-13, 16-14, 16-16, 16-30, 16-31, 16-33, 17-9, 17-13, 17-15, 17-17 to 17-19, 17-23, 17-26, 17-30, 17-37, 17-41, 17-43, 18-2, 18-6, 18-7, 18-11, 18-13, 18-14, 18-16, 18-17, 18-23 to 18-27, 18-29 to 18-31, 18-33, 18-35 to 18-39, 18-42, 18-43, 18-52, 18-53, 18-63, 18-64, 18-67, 18-71, 18-73, 18-79, 18-80, 19-1, 19-2, 19-15, 19-16, 19-18 to 19-20, 19-22, 19-24 to 19-26, 19-28, 19-29, 19-31 to 19-33, 19-36, 19-38, 19-41, 19-44, 19-50, 19-53 to 19-59, 19-65, 19-73, 19-79, 19-80, 19-84, 19-90, 19-92 to 19-95, 20-6, 20-7, 20-9, 20-12, 20-15, 20-23, 20-31 to 20-33, 20-37, 20-39, 20-42, 20-46 to 20-48, 21-7, 21-9, 21-11, 21-12, 21-14, 21-17 to 21-19, 21-22, 21-23, 21-25, 21-26, 22-8 to 22-10, 22-15, 22-16, 22-18 to 22-20, 22-22 to 22-24, 22-28, 22-29, 23-2, 23-3, 23-6, 23-8, 23-11, 23-16, 23-33 to 23-37, 23-43, 23-50, 23-56, 23-61, 23-69, 23-71, 23-73, 23-82, 23-86, 23-91, 23-94, 24-4, 24-6 to 24-9, 24-12, 24-14, 24-16 to 24-18, 24-24 to 24-26, 24-28, 24-30 to 24-33

Volume balance, 18-25, 18-26

Volume-to-capacity ratio, 16-7, 16-8, 16-13, 16-14, 16-16, 17-37, 18-6, 18-7, 18-13, 18-36 to 18-39, 18-67, 18-71, 18-73, 19-1, 19-2, 19-15, 19-18, 19-20, 19-25, 19-29, 19-31, 19-50, 19-53, 19-55 to 19-58, 19-94, 19-95, 20-6, 20-7, 20-48, 21-25, 21-26, 22-9, 22-10, 22-22 to 22-24, 22-29, 23-2, 23-3, 23-6, 23-8, 23-11, 23-16, 23-28, 23-33 to 23-37, 23-43, 23-50, 23-56, 23-61, 23-69, 23-71, 23-73, 23-82, 23-86, 23-91, 23-94, 23-96, 24-4, 24-6

## W

Walk interval, 19-36

Walkway, 16-18, 18-44, 18-46, 18-49, 18-52, 19-73, 19-75, 19-77, 24-1, 24-3, 24-4, 24-6, 24-7, 24-9 to 24-11, 24-13, 24-14, 24-27, 24-28, 24-33

Weaving, 23-66, 23-70, 23-77, 23-79, 23-83, 23-93

Work zone, 17-1, 17-7 to 17-9, 17-12, 17-18, 17-22 to 17-25, 17-30, 17-37, 18-2, 18-3, 18-18, 18-23, 19-2, 19-3, 19-45, 19-48, 19-49

## Y

Yellow change interval, 19-10 to 19-13, 19-36, 19-79, 19-88

Yellow trap, 19-35

Yield point, 23-53, 23-57